

(12) **United States Patent**
Schechter et al.

(10) **Patent No.:** **US 11,932,986 B2**
(45) **Date of Patent:** **Mar. 19, 2024**

(54) **AUTONOMOUS LAUNDRY FOLDING DEVICES, SYSTEMS, AND METHODS OF USE**

(71) Applicant: **Monotony.ai, Inc.**, Allston, MA (US)

(72) Inventors: **Stuart E. Schechter**, Newton, MA (US); **Benjamin D. Bixby**, Newton Highlands, MA (US); **Kevin M. LeBlanc**, Medford, MA (US); **Wilson J. Mefford**, Watertown, MA (US); **Elliot Sinclair Pennington**, Lexington, MA (US); **Laura E. Schwartz**, Newtonville, MA (US); **Jesse Sielaff**, Norfolk, MA (US); **Madeline R. Hickman**, Arlington, MA (US); **Carter J. Ithier**, Hooksett, NH (US); **Samuel Duffley**, Cambridge, MA (US)

(73) Assignee: **Monotony.ai, Inc.**, Watertown, MA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **18/189,438**

(22) Filed: **Mar. 24, 2023**

(65) **Prior Publication Data**
US 2023/0295867 A1 Sep. 21, 2023

Related U.S. Application Data

(63) Continuation of application No. 17/929,840, filed on Sep. 6, 2022, now Pat. No. 11,680,365, which is a (Continued)

(51) **Int. Cl.**
D06F 89/02 (2006.01)

(52) **U.S. Cl.**
CPC **D06F 89/023** (2013.01)

(58) **Field of Classification Search**
CPC D06F 89/02; D06F 89/023; D06F 89/00; D06F 89/005; D06F 89/026; B65H 45/12 (Continued)


(56) **References Cited**
U.S. PATENT DOCUMENTS
2,252,113 A * 8/1941 Moes D06F 89/023 38/135
3,869,073 A 3/1975 Knappe et al. (Continued)

FOREIGN PATENT DOCUMENTS
CA 2687272 C 7/2012
CN 105926257 A 9/2016 (Continued)

OTHER PUBLICATIONS
International Search Report and Written Opinion corresponding to PCT/US2021/039985, dated Nov. 2, 2021, (16 pages). (Continued)

Primary Examiner — Nathan E Durham
(74) *Attorney, Agent, or Firm* — Myers Bigel, P.A.

(57) **ABSTRACT**
A device for autonomously folding a deformable article includes a rotatable platform configured to receive the deformable article and at least one movable elongation in operable communication with at least one elongation drive. The at least one movable elongation is configured to raise and lower from the surface of the rotatable platform, move parallel to the surface, and manipulate the deformable article to thereby fold the deformable article at one of the one or more fold lines. The device includes a table drive configured to rotate the rotatable platform about a central axis such that the at least one elongation aligns with one of the one or more fold lines, and at least one sensor configured to detect the deformable article position and orientation on the rotatable platform. A controller is in operable communication with the (Continued)



at least one elongation drive, the table drive, and the at least one sensor.

32 Claims, 76 Drawing Sheets

Related U.S. Application Data

- continuation of application No. 17/364,533, filed on Jun. 30, 2021, now Pat. No. 11,486,084.
- (60) Provisional application No. 63/168,540, filed on Mar. 31, 2021, provisional application No. 63/168,555, filed on Mar. 31, 2021, provisional application No. 63/106,891, filed on Oct. 29, 2020, provisional application No. 63/046,697, filed on Jul. 1, 2020.
- (58) **Field of Classification Search**
USPC 223/37
See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

3,904,090	A	9/1975	Kannegiesser et al.
5,934,523	A	8/1999	Willett et al.
6,776,316	B2	8/2004	Van et al.
6,826,856	B1	12/2004	Mccabe
8,973,792	B1	3/2015	Selker et al.
9,022,259	B2	5/2015	Breier
2008/0092415	A1	4/2008	Mccabe
2013/0249157	A1	9/2013	Endo et al.
2017/0204555	A1	7/2017	Tanii
2019/0153661	A1	5/2019	Rozov
2019/0309465	A1	10/2019	Rozov
2021/0071353	A1	3/2021	Gabai et al.
2021/0079587	A1	3/2021	Matarasso et al.

FOREIGN PATENT DOCUMENTS

CN	206691509	U	12/2017
CN	105671901	B	4/2018

CN	107974820	A	5/2018
CN	110558739	A	12/2019
CN	110565351	A	12/2019
EP	1690975	A1	8/2006
JP	H01310700	A	12/1989
KR	102026187	B1	9/2019
WO	2008032826	A1	3/2008
WO	2012046227	A1	4/2012
WO	2017060226	A1	4/2017
WO	2017191637	A1	11/2017
WO	2019214754	A1	11/2019

OTHER PUBLICATIONS

#LAUNDRYNERDS, “Expert Session: Automatic Soiled Side Sorting”, YouTube Video, uploaded Jun. 8, 2020, downloaded from <https://www.youtube.com/watch?v=FnGHgJSNY0Q>.

Jensen, “Jenfold Butterfly Fox AF: Automatic unloading, folding and stacking of garments”, Product information; available as of date of filing or Jul. 1, 2020, (6 pages).

Jensen, “State-of-the-art Jensen reference laundry for hotel and restaurant linen”, YouTube Video, uploaded Sep. 9, 2009, downloaded from <https://www.youtube.com/watch?v=OpiFp9i6owY>.

Li, et al., “Multi-Sensor Surface Analysis for Robotic Ironing”, Laundry Robot, Columbia University, Jun. 5, 2020, 2 pages.

Liu, et al., “Cloth Folding Machine”, Mechanical Engineering Design Project Class. 66. <https://openscholarship.wustl.edu/mems411/66>, 2017, 44 pages.

Mypro, “Product Manual: Towel Folder Machine”, Retrieved from: <https://www.myprolaundry.com/product/Towel-Folder-Machine.html>; accessed Jul. 16, 2021, (6 pages).

Thermotron, “Automatic folding & bagging & sealing for casual clothes by (STP950/PV38/KL55)”, YouTube Video, uploaded Jun. 16, 2010, downloaded from <https://www.youtube.com/watch?v=oKgHEz05lqw>.

Thermotron, “Automatic folding machine for garments “STP1000” (clothes folding)”, YouTube Video, uploaded Mar. 10, 2016, downloaded from <https://www.youtube.com/watch?v=Pw49ITNsQrw>.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9A




FIG. 9B




FIG. 10A




FIG. 10B




FIG. 11A




FIG. 11B




FIG. 12






FIG. 13








FIG. 16A




FIG. 16B




FIG. 17




FIG. 18




FIG. 19




FIG. 20A




FIG. 20B




FIG. 20C




FIG. 21




FIG. 22A




FIG. 22B




FIG. 23A




FIG. 23B




FIG. 23C





FIG. 23D






FIG. 24B




FIG. 25

7162 ↗




FIG. 26




FIG. 27A




FIG. 27B




FIG. 28




FIG. 29




FIG. 30




FIG. 31A








FIG. 31B









FIG. 34A




FIG. 34B




FIG. 35




FIG. 36A




FIG. 36B




FIG. 37




FIG. 38




FIG. 39




FIG. 40A




FIG. 40B





FIG. 40C






FIG. 42




FIG. 43




FIG. 44






FIG. 45B

FIG. 45A




FIG. 45D




FIG. 45E




FIG. 46




FIG. 47A




FIG. 47B




FIG. 48A




FIG. 48B







FIG. 49A




7900
↙

FIG. 50




FIG. 51

7900
↙




FIG. 52




FIG. 53




FIG. 54




FIG. 55A




FIG. 55B




FIG. 56




FIG. 57




FIG. 58




FIG. 59




FIG. 60




FIG. 61




FIG. 62




FIG. 63




FIG. 64




FIG. 65




FIG. 66







FIG. 67



68
GG.
F






FIG. 71A




FIG. 71B




FIG. 71C






FIG. 71D






FIG. 72C

AUTONOMOUS LAUNDRY FOLDING DEVICES, SYSTEMS, AND METHODS OF USE

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation application of U.S. patent application Ser. No. 17/929,840 filed Sep. 6, 2022 titled "Autonomous Laundry Folding Devices, Systems, And Methods Of Use," which is a continuation of, U.S. Pat. No. 11,486,084 issued Nov. 1, 2022, titled "Autonomous Laundry Folding Devices, Systems, And Methods Of Use," which claims priority under 35 U.S.C. § 119(e) U.S. Provisional Patent Application Ser. No. 63/046,697 filed Jul. 1, 2020, titled "Autonomous Laundry Folding Device And Methods Of Use," U.S. Provisional Patent Application Ser. No. 63/106,891 filed Oct. 29, 2020, titled "Autonomous Devices, Systems, And Methods For Handling Folded Laundry," U.S. Provisional Patent Application Ser. No. 63/168,540 filed Mar. 31, 2021, titled "Autonomous Devices, Systems, And Methods For Packing Folded Laundry," and U.S. Provisional Patent Application Ser. No. 63/168,555 filed Mar. 31, 2021, titled "Autonomous Devices, Systems, And Methods For Queuing Folded Laundry," the entirety of each of these applications is hereby incorporated by reference.

BACKGROUND

The present disclosure is directed to robotic laundry devices, systems, and methods.

Automating and outsourcing mundane, time-consuming household chores to robotic devices is increasingly common. Time-saving home robots include, for example, floor vacuuming and floor washing robots. Outsourcing responsibilities include, for example, engaging grocery shopping and delivery, and manually operated and human-operator dependent laundry washing and dry-cleaning pick up and return services.

Many homes are appointed with a dedicated washer and dryer for family use. Domestic washers and dryers are increasingly sophisticated and include IoT connectivity features and push notifications for alerting users about cycle progress and energy and resource usage. These technologically advanced machines, however, require human interaction and cannot eliminate the time and manual labor required for processing loads of laundry in the home. Although more modern, "high efficiency" machines are equipped with sensors for metering water usage and dryer temperatures, the efficiency gains are capped by the constraints of sequentially processing single loads of laundry. Additionally, grey water is output to the city water and sewer system for mitigation with each load of laundry processed, and energy is consumed with each load of laundry washed and dried.

Households can outsource laundry chores to laundromat facilities for a fee in exchange for time. Laundromats offering residential mixed load laundering services, however, require human interaction for intake and sorting of dirty laundry, transferring loads from washer to dryer, and then manually folding clean laundry. These are costly processes as measured in time, energy consumption, water consumption, and wastewater output, and they rely on human intervention to keep the process running at every transition and throughout several process steps. This invites delays at every stage. Because these processes are human-dependent and inefficient, the costs are passed along to the customers outsourcing their laundry for cleaning. Human-

reliant laundering services also require that employees touch the belongings of the customer, potentially exposing the employee to contaminants in the dirty laundry and potentially exposing the clean laundry to transferable pathogens, dust, hair, and other debris emanating from a laundromat employee. In addition to potentially introducing undesirable contact contamination from the employees processing the loads of laundry, a privacy barrier is breached. Outsourcing household laundry to a laundromat involves employees interacting with customers' personal belongings including bodily worn garments.

Industrial laundry services exist for handling uniform business-related items, such as hospital bed sheets, medical scrubs, and hotel towels. Such industrial machines are tailor-made to accept one type of laundry item of one size or style. For example, unique folding machines exist to accept one of washed flat sheets, fitted sheets, hotel towels, and hotel bathrobes. These machines require human operators to load the washed article into its dedicated machine, which is sized and designed to fold that one type and/or size of article. This type of process line relies on a human operator for properly aligning and loading the clean article into the machine, which could introduce bodily contaminants, bacteria, and viral matter into the clean articles. Like laundromat services, these industrial services rely on human intervention and potentially introduce bio-contaminants into clean loads of laundry. Because these services are only profitable by processing large volumes of like items, these industrial processors are generally subscription-based services for large clients like hotels and hospitals producing standard-size, repeat laundry articles and are not available to consumers at an individual household level. Additionally, these services are configured to combine laundry from more than one source and are not configured to isolate and process separate loads for individual households.

Autonomous robotic devices are provided to process loads of household laundry. Such devices eliminate human contact with deformable laundry articles and autonomously process batches of disparate article types and sizes. As such, the devices need to be designed to be efficient and reliable for replacing the common, human-dependent chore of laundry.

SUMMARY

In one example, a device for autonomously folding a deformable article includes a rotatable platform configured to receive the deformable article, at least one clamp rod, a table drive and at least one movable sweep rod. The at least one clamp rod is configured to raise and lower from a surface of the rotatable platform and slidably move parallel to the surface. The at least one clamp rod is in operable communication with at least one clamp drive and is configured to clamp the deformable article to the surface in a lowered position. The table drive is configured to engage the rotatable platform and rotate the platform about a central axis such that the at least one clamp rod aligns with a first clamp position for the deformable article. The at least one movable sweep rod is disposed parallel to the at least one clamp rod and is in operable communication with at least one sweep drive. The at least one movable sweep rod is configured to raise and lower from the surface of the rotatable platform, slidably move parallel to the surface, slide under an unclamped portion of the deformable article, lift the unclamped portion above the at least one clamp rod, pass the unclamped portion over the at least one clamp rod,

and dispose the free end to a resting position atop another portion of the deformable article.

Implementations of the device may include one or more of the following features.

In examples, the received deformable article is substantially extended. The deformable article is received from a repositioning device adjacent the rotatable platform, the repositioning device being configured to extend the deformable article for folding.

In examples, the received deformable article is one of a plurality of deformable laundry articles comprising two or more article types of at least one of different sizes and different shapes. The plurality of deformable laundry articles can include one or more loads of household laundry. Each of the two or more article types can comprise a longest dimension of between about 4 cm to 500 cm.

In examples, the platform has a shortest dimension in a range of between about 0.5 m to 5 m.

In examples, the platform is circular and the shortest dimension is a diameter.

In examples, the platform includes a continuous flat surface. The continuous flat surface can be opaque. The continuous flat surface can include at least one of a color and pattern. The platform can include a cross sectional thickness of between about 0.5" to 2". The platform can include and/or be manufactured from at least one of foam core, polystyrene, balsa wood, bamboo, aluminum, stainless steel, sign board, and ULTRABOARD.

In examples, the table drive is configured to rotate the platform at a fastest speed in a range of between about 30 RPM to 120 RPM. The table drive can be reversible and configured to rotate the platform in at least one of a forward direction and reverse direction.

In examples, the device further includes a first pair of parallel support rails disposed adjacent the platform. The at least one clamp rod is configured to engage a first carrier slidably disposed on an inner one of the pair of parallel support rails and the at least one sweep rod is configured to engage a second carrier slidably disposed on an outer one of the parallel rails. Alternatively, the at least one clamp rod can be configured to engage the second carrier slidably disposed on the outer one of the pair of parallel support rails and the at least one sweep rod can be configured to engage the first carrier slidably disposed on the inner one of the parallel rails. The first and second carrier each further include a linear drive configured to raise and lower the engaged at least one retractable clamp rod and at least one sweep rod. The drive can be at least one of a belt drive, chain and sprocket, a screw drive, and a pneumatic drive. The first carrier can be configured to cantilever the engaged at least one clamp rod above the rotatable platform. The first carrier further comprises a pivot joint for tilting the engaged at least one clamp rod above the rotatable platform. In examples, the at least one clamp rod is retractable and the first carrier further includes at least one friction wheel configured to engage the clamp rod for extending and retracting over the platform. In examples, the at least one clamp rod is telescoping and configured to extend and retract over the platform. Additionally or alternatively, the first carrier can further comprise a pivot joint for tilting the engaged at least one clamp rod above the rotatable platform. The first and second carriers can be configured to engage with the corresponding clamp drive and sweep drive. The first and second carriers can be configured to slide along the first pair of parallel support rails at drive rate of between about 5 mm/s to 3 m/s.

In examples, the device further includes a second pair of parallel support rails disposed parallel to the first pair of parallel support rails and adjacent the rotatable platform, the rotatable platform being disposed between the first pair and second pair of parallel support rails. In examples, the at least one clamp rod includes a first clamp rod engaged with the first carrier and a second clamp rod engaged with a third carrier slidably engaged with one of the second pair of support rails. The third carrier slidably can be engaged with an inner one of the second pair of parallel support rails. Alternatively, the third carrier slidably can be engaged with an outer one of the second pair of parallel support rails. The first and second clamp rods can be configured to slide synchronously. The first and second clamp rods can be configured to slide asynchronously. The first and second clamp rods can be configured to extend and retract synchronously. A longitudinal axis of each of the first and second clamp rods can align with a shared axis. The first and second clamp rods can include a gap therebetween in a range of between about 0 to 50 mm in a fully extended position. In examples, the at least one clamp rod includes a single clamp rod engaged with the first carrier and a third carrier slidably engaged with an inner one of the second pair of parallel support rails such that the single clamp rod extends across the entire rotatable platform. The at least one clamp rod can be retractable and the first carrier can further include at least one friction wheel configured to engage the clamp rod for extending and retracting over the platform. The at least one clamp rod can be telescoping and configured to extend and retract over the platform.

In examples of at least one of a retractable and telescoping single clamp rod, the third carrier can be configured to selectively receive and release the single clamp rod when fully extended. In examples, the first carrier further includes a pivot joint for tilting the engaged at least one clamp rod above the rotatable platform and the third carrier is configured to selectively receive and release the single clamp rod when tilted to a lowered position.

In examples, the at least one sweep rod comprises a first sweep rod engaged with the second carrier and a second sweep rod configured to engage with a fourth carrier slidably engaged with one of the second pair of parallel support rails. In examples, the fourth carrier is slidably engaged with an outer one of the second pair of parallel support rails. In examples, the fourth carrier is slidably engaged with an inner one of the second pair of parallel support rails. In examples, the at least one sweep rod comprises a single sweep rod engaged with the second carrier and a fourth carrier slidably engaged with an outer one of the second pair of parallel support rails, the single sweep rod extending across the entire rotatable platform.

In examples, the device further includes a rotating drive configured to rotate the at least one movable sweep rod about a longitudinal axis at least one of parallel to or coaxial with a longitudinal central axis of the sweep rod while slidably moving along the sweep slide rail. In examples, the at least one movable sweep rod is configured to slide under a terminal edge of the unclamped portion of the garment while rotating. In examples, at least one movable sweep rod rotates under the deformable article clockwise while sliding from the right of the at least one clamp rod to left and counterclockwise while sliding from the left of the at least one clamp rod to right. In examples, the at least one movable sweep rod rotates in a range of about 5 to 500 RPM.

In examples, the at least one clamp rod and at least one movable sweep rod each comprise a shaped cross section. The shaped cross section can include at least one of circular,

5

rectangular, square, diamond, triangular, oval, pentagonal, hexagonal, spline, and octagonal. In examples, the shaped cross section includes a largest dimension of between about 2 mm and 25 mm.

In examples, the at least one clamp rod and at least one movable sweep rod each include, or are manufactured from, at least one of wood, stainless steel, aluminum, DELRIN, polycarbonate, graphite, titanium, PVC, bamboo, and chromoly.

In examples, the device further includes a force sensor in operable communication with the at least one clamp drive configured to limit the applied clamping force to a range of between about 2.5 N and 50 N.

In examples, the device further includes one or more sensors configured to at least one of detect one of one or more features and capture one or more images of the deformable article disposed on the rotatable platform. In examples, the device further includes a controller in operative communication with the table drive, the at least one clamp drive, the at least one sweep drive, and one or more sensors disposed about the surface. The one or more sensors can include at least one of a 3-D camera, an IR sensor, a 2-D camera, LIDAR, LADAR, a sonar proximity sensor, an ultrasonic ranging sensor, a radar sensor (e.g., including Doppler radar and/or millimeter-wave radar), and a pair of stereo depth cameras. The one or more sensors can be configured to output 3-D image data to the controller. The one or more sensors can be configured to output one or more 2-D images to the controller.

In examples, the controller is further configured to determine, based on a comparison of a received output signal of the one or more sensors to data stored in a memory in communication with the controller, at least one of an article type, a front side, a back side, and an inside surface of the deformable laundry article. The at least one of the one or more sensors can be a 2-D camera and the data associated with repositioned deformable laundry article is size invariant image data. The at least one of the one or more sensors can be a 3-D camera and the memory further comprises a neural network.

In examples, the controller is configured to receive one or more output signals from the one or more sensors, determine, based on the received one or more output signals, at least one of an article type and size of the deformable article, determine, based at least on the at least one of the determined article type and determined article size, a fold line of the deformable article, instruct a drive motor to rotate the platform to align the fold line of the deformable article with the at least one clamp rod suspended above the platform, and instruct the at least one clamp rod to lower onto the first fold line, the lowered at least one clamp rod configured to apply force and immobilize the fold line of the deformable laundry article against the surface. The controller is further configured to instruct the at least one movable sweep rod to slidably move in a first direction between the deformable article and the surface to a position adjacent and parallel to the at least one retractable clamp rod, and raise the deformable article up and over the at least one retractable clamp rod, slidably moving in the first direction at least until the article disengages from the at least one movable sweep rod. In examples, aligning the fold line of the deformable article with the at least one clamp rod comprises rotating the fold line to a substantially parallel position with the at least one clamp rod.

In examples, the fold lines include a line across at least a portion of the deformable article about which the deform-

6

able article is configured to fold. The fold line crosses two outer edges of at least a portion of the deformable article.

In examples, the at least one clamp rod is retractable and configured to extend and retract over the platform. In examples, the at least one clamp rod is telescoping. In examples, the at least one clamp rod engages a driven friction wheel configured to advance and retract the at least one clamp rod. In examples, after the article disengages from the at least one movable sweep rod, the controller is further configured to instruct the clamp rod to retract until disengaged from the deformable article.

In one example, a method of robotically folding a deformable article, includes iterating a folding sequence one or more times, and stopping iterating the folding sequence upon the determining the article comprises the at least one final fold dimension. The folding sequence includes receiving, at a controller, one or more output signals from one or more sensors in communication with the controller, the one or more sensors being configured to at least one of detect one of one or more features and capture one or more images of a deformable article disposed on a platform, determining, based on the at least one of one or more features and one or more images, at least one of an article type and an article size, determining a fold line of the deformable article, instructing a drive motor to rotate the platform to align the fold line of the deformable article with a clamp suspended above and elongated parallel to a surface of the platform, instructing the clamp to lower onto the fold line, the lowered clamp configured to apply force and immobilize the fold line of the deformable article against the surface, and instructing an elongated sweep rod to move. Instructing the elongated sweep rod to move includes instructing the elongated sweep rod to slidably move in a first direction toward the clamp to a position adjacent and parallel to the clamp, the elongated sweep rod being disposed between the deformable article and the surface and rotating about a longitudinal axis while slidably moving, raise the deformable article up and over the clamp while slidably moving in the first direction at least until the article disengages from the elongated sweep rod, retract the clamp until disengaged from the article, and determine whether the article includes the at least one final fold dimension.

Implementations of the method may include one or more of the following features.

In examples, the fold line includes a corresponding line across at least a portion of the deformable article about which the deformable article is configured to fold. In examples, the fold line crosses two outer edges of at least a portion of the deformable article.

In examples, the drive motor is configured to operate bi-directionally and wherein instructing the drive motor to rotate the platform includes rotating the platform at least one of in a forward direction and in a reverse direction.

In examples, the method further includes rotating the sweep rod while slidably moving. In examples, the at least one movable sweep rod is configured to slide under a terminal edge of the unclamped portion of the garment while rotating. In examples, the elongated sweep rod comprises a circular cross section and rotates about a central axis. In examples, the elongated sweep rod rotates under the deformable article clockwise while sliding from the right of the at least one clamp rod to left and counterclockwise while sliding from the left of the at least one clamp rod to right. Additionally or alternatively, the elongated sweep rod rotates under the deformable article counterclockwise while sliding from the right of the at least one clamp rod to left and clockwise while sliding from the left of the at least one

clamp rod to right. In examples, the sweep rod rotates in a range of about 5 to 500 RPM.

In examples, the method further includes receiving input from a force sensor in operable communication with the at least one clamp drive configured to limit the applied clamp-
5 ing force to a range of between about 2.5 N and 50 N.

In examples, the method further includes determining the fold line based on at least one of the article type and the article size. In examples, the method further includes the controller determining the at least one final folded dimension of the article by identifying in a memory store one or more pre-determined final folded dimensions associated with the determined at least one of the article type and the article size.

In examples, the at least one final folded dimension is dynamically selected based on the determined at least one of article type and article size and determining the fold line is based at least in part on the dynamically selected final folded dimension.

In examples, the one or more features comprise natural fold lines. In implementations, the method further includes determining the fold line based on one or more natural fold lines of the deformable article. In implementations, the one or more natural fold lines comprises a bisector of the deformable article.

In examples, determining the article type includes processing the received output signal of the one or more sensors with a neural network classifier. In examples, the one or more sensors comprises at least one of a 3-D camera, an IR sensor, a 2-D camera, LIDAR, LADAR, a sonar proximity sensor, an ultrasonic ranging sensor, a radar sensor (e.g., including Doppler radar and/or millimeter-wave radar), and a pair of stereo depth cameras. In examples, the controller is configured to receive an output signal comprising 3-D image data of the deformable article. Alternatively or additionally, in examples, the controller is configured to receive an output signal comprising one or more 2-D images of the deformable article. In examples, determining article type comprises performing a size invariant imagery comparison to classified images stored in a memory in communication with the controller. In examples, the controller is further configured to determine, based on a comparison of a received output signal of the one or more sensors to data stored in a memory in communication with the controller, at least one of an article type, a front side, a back side, and an inside surface of the deformable laundry article

In examples, the one or more sensors comprises at least one of a 3-D camera, an IR sensor, a 2-D camera, LIDAR, LADAR, a sonar proximity sensor, an ultrasonic ranging sensor, a radar sensor (e.g., including Doppler radar and/or millimeter-wave radar), and a pair of stereo depth cameras. In implementations, the controller is configured to receive an output signal comprising one or more 2-D images of the deformable article, and determining the article type comprises performing a size invariant imagery comparison to classified images stored in a memory in communication with the controller.

In examples, the method further includes receiving an output signal comprising a 3-D image data of the deformable article and determining, based on the 3-D image data, one or more critical features of the deformable article. In implementations, the one or more critical features includes a portion of the deformable article comprising at least one of a raised prominence, a closure, and an affixed embellishment.

In examples, determining the fold line includes, based on the output signal of each of the one or more sensors,

determining one or more natural fold lines of the deformable article. In implementations, the one or more natural fold lines includes a bisector of the deformable article.

In implementations, the one or more natural fold lines includes a seam of the deformable article.

In examples, the method further includes, determining, based on the article type, a sequence of instructions for smoothing the deformable article prior to folding, the sequence of instructions being executable by the controller and stored on a memory in communication with the controller. In implementations, the sequence of instructions for smoothing the deformable article prior to folding includes instructing a drive motor to rotate the platform to align an anchor location of the deformable article with the clamp
10 suspended above and elongated parallel to a surface of the platform, instructing the clamp to lower onto the anchor location, the lowered clamp configured to apply force and immobilize the anchor of the deformable laundry article against the surface, and instructing the elongated sweep rod to slidably move in a first direction toward the clamp to a position adjacent and parallel to the clamp, the elongated sweep rod being disposed between the deformable article and the surface and rotating about a longitudinal axis while slidably moving, raise the deformable article up above the surface of the platform, and slidably move in a second direction opposite the first direction until the elongated sweep rod disengages from the deformable article. In examples, the sequence of instructions for smoothing further includes instructing the elongated sweep rod to slidably move in the first direction to the position adjacent and parallel to the clamp, lower to contact the deformable article, and slidably move in a second direction opposite the first direction until the elongated sweep rod disengages from the article. In examples, the anchor location comprises the fold line. In any of the preceding examples and implementations, the sweep rod can rotate counterclockwise for the first motion comprising a right to left movement and clockwise for the first motion comprising a left to right movement. Additionally or alternatively, in any of the preceding implementations, the sweep rod can rotate counterclockwise for the first motion comprising a right to left movement and clockwise for the first motion comprising a left to right movement. In examples, in any of the preceding examples and implementations the method further comprising repeating the sequence of instructions for smoothing, the repeated sequence comprising at least one of sliding and rotating the elongated sweep rod at a relatively slower rate than a first execution of the sequence of instructions for smoothing. In any of the preceding examples and implementations, the anchor location comprises a middle location of the deformable article and the sequence of instructions for smoothing the deformable article prior to folding is executed by the controller on both sides of the anchor location.

In implementations, the method further includes comparing the received output signal to data stored in a memory in communication with the controller for determining the article type. The method can further include identifying features indicative of at least one of a front side and a back side of the deformable article. In examples, the method can further include identifying features indicative of the deformable article being inside out. The identifiable features indicative of the deformable article being inside out can include at least one a visible seam, a tag, and stitching.

In examples of the method, the deformable article is one of a plurality of deformable laundry articles including two or more article types of at least one of different sizes and different shapes. Each of the two or more article types can

include a longest dimension of between about 4 cm to 500 cm. In examples, the platform is configured to receive a plurality of deformable articles including alternating non-identical article types of the two or more article types.

In examples, the method is configured to be executed autonomously by the controller, and the controller is configured to be in operative communication with the one or more sensors, the drive motor of the rotatable platform, the clamp, and the elongated sweep rod. In examples, the controller is configured to communicate with a network via at least one of wired and wireless communication protocols. In implementations, the method further includes receiving one or more folding instructions from a remote device in operable communication with the network. The one or more folding instructions can include user inputs to at least one of a computer portal and smartphone application representative of one or more user inputs. The one or more user inputs can include at least one of a preferred at least one final dimension for the deformable article, a request for not folding the deformable article, a submission of an article type for the deformable article, one or more specified fold lines, and a preferred sequence for folding the deformable article at each of the one of the one or more specified fold lines.

In examples, the method further includes communicating with a packing robot configured to receive the deformable article from the platform upon stopping iterating the folding sequence.

In examples, the method further includes instructing a packing robot in communication with the network to retrieve the deformable article upon stopping iterating the folding sequence.

In examples, the method further includes instructing a tilt motor of the platform to tilt the platform to slidably release the deformable article to a receiving platform upon stopping iterating the folding sequence.

In one example, a method of robotically flattening a deformable article for folding includes receiving, at a controller, one or more output signals from one or more sensors in communication with the controller, the one or more sensors being configured to at least one of detect one of one or more features and capture one or more images of a deformable article disposed on a platform. The method includes instructing a drive motor to rotate the platform to align an anchor location of the deformable article with a clamp suspended above and elongated parallel to a surface of the platform, instructing the clamp to lower onto the anchor location, the lowered clamp configured to apply force and immobilize the anchor location of the deformable laundry article against the surface, and instructing an elongated sweep rod to move. Instructing the elongated sweep rod to move includes instructing the elongated sweep rod to slidably move in a first direction toward the clamp to a position adjacent and parallel to the clamp, the elongated sweep rod being disposed between the deformable article and the surface and rotating about a longitudinal axis while slidably moving, raise the deformable article up above the surface of the platform, and slidably move in a second direction opposite the first direction until the elongated sweep rod disengages from the deformable article.

Implementations of the method may include one or more of the following features.

In examples, the method further includes instructing the elongated sweep rod to slidably move in the first direction to the position adjacent and parallel to the clamp, lower to contact the deformable article, and slidably move in a second direction opposite the first direction until the elongated sweep rod disengages from the article.

In any of the preceding examples, the method further includes determining at least one of an article type and an article size. In examples, the method further includes determining, based on at least one of the article type and the article size, at least one final folded dimension of the article.

In examples, the method further includes iterating a folding sequence one or more times and stopping iterating the folding sequence upon the determining the article comprises the at least one final fold dimension. In examples, the folding sequence includes determining a fold line of the deformable article, instructing a drive motor to rotate the platform to align the fold line of the deformable article with the clamp suspended above and elongated parallel to a surface of the platform, instructing the clamp to lower onto the fold line, the lowered clamp configured to apply force and immobilize the fold line of the deformable laundry article against the surface, and instructing the elongated sweep rod move. In examples, instructing the elongated sweep rod to move includes instructing the sweep rod to slidably move in a first direction toward the clamp to a position adjacent and parallel to the clamp, the elongated sweep rod being disposed between the deformable article and the surface and rotating about a longitudinal axis while slidably moving, raise the deformable article up and over the clamp while slidably moving in the first direction at least until the article disengages from the elongated sweep rod, retract the clamp until disengaged from the article, and determine whether the article comprises the at least one final fold dimension.

In examples, the at least one final folded dimension of the article is dynamically determined. In implementations, the at least one final folded dimension of the article is determined by a remaining volume in a packing container configured to receive the article from the platform. In implementations, the at least one final folded dimension of the article is stored in a database including a plurality of final folded dimensions associated with at least one of article type and article size.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 depicts a schematic of an example autonomous robotic laundry process line.

FIG. 2 depicts a schematic example of a system for controlling an autonomous robotic process line.

FIG. 3 depicts a system level schematic of an example autonomous folding device.

FIG. 4 depicts an orthogonal view of an example of a folding device.

FIG. 5 is a top view of FIG. 4.

FIG. 6 is a perspective bottom view of FIG. 4.

FIG. 7 is a magnified partial view of FIG. 6 showing a drive motor for rotating a platform of the folding device.

FIG. 8 is an example schematic of rotational positions of a folding platform.

FIGS. 9A and 9B depict an example motion sequence of a rotating folding platform to orient an article thereon relative to a clamp rod.

FIG. 10A depicts a top view of an example a folding device.

FIG. 10B depicts a side view of the example of a folding device of FIG. 10A.

FIG. 11A depicts an example schematic side view of movable rods the folding device of FIGS. 10A-B in a starting position for folding an article over a clamp rod.

FIG. 11B depicts an example of a raised article position during a folding sequence of folding a deformable article over a clamp rod.

11

FIG. 12 depicts an example of the raised article of FIG. 11B being folded over the clamp rod.

FIG. 13 depicts an example of the article of FIG. 12 being folded over the clamp rod while a sweep rod moves to disengage from the folded article.

FIG. 14 depicts a close-up partial view of example clamp and sweep rod carriers of the folding device.

FIG. 15 depicts a perspective view of example clamp rods, clamp carriers, and clamp support rails of the folding device.

FIG. 16A depicts an end view schematic of an example clamp rod and carrier.

FIG. 16B depicts a perspective side view schematic of an example clamp rod and carrier.

FIG. 17 depicts a side view of an example folding device including carrier pivots for raising the clamp rods at an angle to the platform.

FIG. 18 depicts a close-up partial view of an example clamp rod, clamp rod carrier, clamp rod support rail, and drive motors of the folding device.

FIG. 19 depicts the example clamp rod of FIG. 18 supported by a pair of carriers and support rails.

FIG. 20A depicts a side view schematic of an example start of a motion sequence of a rotating clamp rod of FIGS. 18 and 19 approaching an edge of a clamped article to slide therebeneath without bunching the fabric of the article.

FIG. 20B depicts a side view schematic of the rotating clamp rod of FIG. 20A engaging and lifting the edge of a clamped article to slide therebeneath without bunching the fabric of the article.

FIG. 20C depicts a side view schematic of the rotating clamp rod of FIG. 20B sliding beneath the article to a position adjacent a clamp rod without bunching the fabric of the article.

FIG. 21 depicts an example schematic of a neural network configured to be utilized by a folding device of FIGS. 10A-B.

FIG. 22A depicts a schematic example of folding a shirt sequentially along fold lines to arrive at a target folded article size and shape.

FIG. 22B depicts a schematic example of folding a tank top sequentially along fold lines to arrive at a target folded article size and shape.

FIG. 23A depicts a schematic example of flattened pants needing folding.

FIG. 23B depicts a schematic example of fold lines along which the pants of FIG. 23 will be sequentially folded.

FIG. 23C depicts a schematic example of the pants of FIG. 23B folded along a first sequentially executed fold line.

FIG. 23D depicts a schematic example of the pants of FIG. 23C folded along a second sequentially executed fold line and a third fold line indicated for a final fold to a target folded article size.

FIG. 24A depicts a top view of an example of a folding device.

FIG. 24B depicts a side view of the example of a folding device of 24A.

FIG. 25 depicts an example method of folding executed by a controller of the folding device.

FIG. 26 depict an example mask generated by the controller executing the method of folding of FIG. 25.

FIG. 27A depicts an example shipping container for containing one or more folded articles for return to a customer.

FIG. 27B depicts example target rectangle sizes to which one or more articles are folded to fit within the example shipping container of FIG. 27A.

12

FIG. 28 depicts a perspective view of an example schematic of casting shadows on an article for wrinkle detection and article edge detection.

FIG. 29 depicts an example side view schematic of casting shadows on an article disposed on a platform of a folding device for article outline detection.

FIG. 30 depicts an example method of smoothing a deformable article prior to folding.

FIG. 31A depicts a schematic side view of an underside sweep of a clamped article during smoothing on a first side of a clamp.

FIG. 31B depicts a schematic side view of an overside sweep of the clamped article of FIG. 31A on the first side of the clamp.

FIG. 32A depicts a schematic side view of an underside sweep of the clamped article of FIGS. 31A-B during smoothing on a second side of a clamp.

FIG. 32B depicts a schematic side view of an overside sweep of the clamped article of FIG. 32A on the second side of the clamp.

FIGS. 33A-33C depict an example sequence of smoothing a clamped shirt in a first orientation relative to clamp and sweep rods.

FIGS. 34A-34B depict an example sequence of smoothing the clamped shirt of FIGS. 33A-C in a second orientation rotated from the first orientation relative to clamp and sweep rods.

FIG. 35 depicts the shirt of FIGS. 33A-34B at the completion of smoothing with wrinkles smoothed flat.

FIGS. 36A-B depict an example sequence of smoothing pants sequentially on either side of a clamp rod to remove wrinkles and straighten twisted and/or angular protrusions.

FIG. 37 depicts the pants of FIGS. 36A-36B at the completion of smoothing.

FIG. 38 depicts an example method executable by a controller of the folding robot for determining target folded dimensions for a shirt in accordance with a particular article type fold routine of the folding method of FIG. 25.

FIG. 39 depicts an example method of folding a shirt to the target folded dimensions determined by the method of FIG. 38.

FIGS. 40A-40C schematically depict example dimensions and sequentially folded states of a shirt in accordance with the methods of FIGS. 38-39.

FIG. 41 depicts an example method executable by a controller of the folding robot for determining target folded dimensions for pants in accordance with a particular article type fold routine of the folding method of FIG. 25.

FIG. 42 depicts an example method of folding pants in accordance with a default half fold method to the target folded dimensions determined by the method of FIG. 41.

FIG. 43 depicts an example half fold method of folding pants.

FIG. 44 depicts an example thirds fold method of folding pants.

FIG. 45A depicts a schematic example measured dimensions and target folded dimensions of flattened pants for use in the methods of FIGS. 41-44.

FIGS. 45B-C schematically depict example sequentially folded states of a pants in accordance with the half fold methods of FIG. 43.

FIGS. 45D-E schematically depict example sequentially folded states of a pants in accordance with the thirds fold method of FIG. 44.

13

FIG. 46 depicts an example method executable by a controller of the folding robot for folding an article according to a general fold in protrusions routine of the folding method of FIG. 25.

FIG. 47A depicts a schematic example of a controller generated mask and identification of a core rectangle and vectors defining the fold directions of protrusions into the core rectangle in accordance with the method of FIG. 46.

FIG. 47B depicts a schematic example of a controller generated mask and a plot of distances from an outer perimeter to the core rectangle for identifying protrusions and executing the method of FIG. 46.

FIG. 48A depicts a schematic example of a method executable by a controller of the folding robot for folding an article according to a general fold area to target size routine of the folding method of FIG. 25.

FIG. 48B depicts an example cross section schematic of an article bent around a clamp rod at a bend radius.

FIGS. 49A-D sequentially schematically depicts an example method executable by a controller of the folding robot for folding an article according to a general recursive fold in half routine of the folding method of FIG. 25.

FIGS. 50 through 54 depict example user interfaces for remote customer interaction with the folding device.

FIG. 55A depicts a top-down view of an example transit conveyor for delivering a repositioned article to a folding device.

FIG. 55B depicts a side view of an example transit conveyor for delivering a repositioned article to a folding device.

FIG. 56 depicts a side view of a transit conveyor approaching the folding device with a repositioned article.

FIG. 57 depicts a side view of the transit conveyor of FIG. 56 delivering the repositioned article to the folding device.

FIG. 58 is a schematic of overlapping portions of an example repositioning robot conveyor and a transit conveyor of an autonomous robotic laundry process line.

FIG. 59 depicts a top-down schematic example of a retrieving conveyor for extracting a folded article from a folding device.

FIG. 60 depicts a side view of the retrieving conveyor approaching the folding device of FIG. 59.

FIG. 61 depicts a side view of the retrieving conveyor of FIG. 60 extracting the repositioned article from the folding device.

FIG. 62 depicts a top view of an example a folding device including a folding blade suspended over a folding platform.

FIG. 63 depicts a perspective front view of the example folding device of FIG. 62.

FIG. 64 depicts a perspective rear view of the example folding device of FIGS. 62 and 63.

FIG. 65 depicts a close-up partial view of a blade assembly of the folding device of FIGS. 62-64.

FIG. 66 depicts a top cross section schematic of an end of a blade assembly of the folding device of FIGS. 62-64.

FIG. 67 depicts a perspective view of the blade assembly of the folding device of FIGS. 62-64 with the blade rotated to a horizontal position.

FIG. 68 depicts a perspective view of the blade assembly of FIG. 67 with the blade rotated past horizontal position to an angled position relative to a folding device platform.

FIG. 69 depicts an alternative schematic example of a pre-tensioned blade support structure of the blade assembly of FIGS. 62-64.

FIG. 70 depicts another alternative schematic example of a pre-tensioned blade support structure of the blade assembly of FIGS. 62-64.

14

FIGS. 71A-D depict a sequential schematic side view of the folding device executing a method of an underside sweep of a clamped article with the rotatable blade of the folding device of FIGS. 62-64.

FIGS. 72A-72C depict a folding sequence of a clamped article using the rotatable blade of the folding device of FIGS. 62-64.

DETAILED DESCRIPTION

This disclosure relates to autonomous robotic devices, systems, and methods for handling residential loads of laundry. The system includes one or more autonomous process lines comprising a plurality of robotic devices configured to work in concert to process a dirty load of household laundry from a mass of dirty, non-uniform articles to individually separated, cleaned, and folded laundry articles. The plurality of robotic devices operate without human intervention to efficiently and effectively launder a customer's dirty items. This disclosure relates to autonomous robotic devices configured to autonomously fold clean, deformable laundry articles for introduction to an autonomous packing robot. The autonomous robotic devices are configured to fold a plurality of loads of laundry each comprising a plurality of deformable article types. The laundry articles are collected from a household and delivered to the process line for cleaning. The autonomous processes are time and cost efficient, eliminate human intervention-based delays, eliminate line workers and associated introduction of human contaminants introduced by line workers, and eliminate any concerns with having private personal items handled by strangers.

As shown in FIG. 1, in implementations of the system, a process line 100 comprises a plurality of autonomous robots configured to operate in series without human intervention to process and transport dirty laundry through the cleaning process and fold and repack the clean laundry for return to a household. In one implementation, the process line 100 comprises an autonomous intake robot 2000 for receiving a load of dirty household laundry comprising a plurality of deformable laundry articles. The deformable laundry articles can be non-uniform in type, size, shape, color, and fabric and can require particular treatment and handling. For example, the plurality of deformable laundry articles can include items commonly laundered in homes, such as sheets, towels, table cloths, and adult and children's garments, for example, tee shirts, pants, socks, undergarments, hooded sweatshirts, baby socks, wash cloths, dresses, open front dress shirts, and blouses. The autonomous intake robot 2000 is configured to introduce the plurality of deformable laundry articles to a separating and sorting robot 3000 configured to separate out each one of the deformable laundry articles of the plurality of deformable laundry articles pertaining to a single customer and/or household. In implementations, the separating and sorting robot 3000 is configured to sort each one of the separated deformable laundry articles into one or more related batches for washing. In implementations, the separating and sorting robot 3000 is configured to intelligently batch the separated each one of the deformable laundry articles into its own dedicated load or into a load with at least one other separated deformable laundry article according to a programmed sorting algorithm. The programmed sorting algorithm can be based, for example, on criteria including at least one of material color, material type, customer washing preference, water temperature requirements, and load size. In implementations, the separating and sorting robot 3000 is configured to identify and record the number and types of

15

garments in the load of laundry and provide this information to one or more robots in the process line 100.

The separating and sorting robot 3000 outputs one or more intelligently sorted batches of deformable laundry articles to one or more washing and drying robots 4000 for laundering. The one or more washing and drying robots 4000 output the clean laundry articles to a clean laundry separating robot 5000. Implementations of the clean laundry separating robot 5000 can be similar or identical to the separating and sorting robot 3000. The clean laundry separating robot 5000 is configured to separate a load of clean laundry into individual deformable laundry articles for introduction into a repositioning robot 6000. In implementations to be described herein in detail, the repositioning robot 6000 receives a single deformable laundry article and manipulates and repositions it for automated introduction into a folding robot 7000, which automatically folds the laundry article for introduction to a packing robot 8000. In implementations, the packing robot 8000 automatically packs the clean load of laundry comprising the plurality of clean and folded deformable laundry articles in a shipping container for automated redistribution to the customer. In implementations, the shipping container is a reusable container. In implementations, the shipping container is a disposable container. In implementations, the shipping container is a non-deformable container with an ingress protection rating that includes an intrusion protection rating of 5 or 6 and a moisture protection rating of any and all of 1 through 6 in accordance with the Ingress Protection Code, IEC standard 60529.

Implementations of the process line 100a of household laundry cleaning robots can comprise one or more of each of the robots depicted in FIG. 1. In implementations, each autonomous process line 100 can include a cluster of washing and drying robots 4000a-n. In other implementations, the autonomous process line 100 includes a cluster of washing and drying robots 4000a-n shared by two or more sets of automated intake robots 2000 and dirty laundry separating and sorting robots 3000 and two or more sets of clean laundry separating robots 5000, repositioning robots 6000, folding robots 7000, and packing robots 8000. Additionally or alternatively, a process line can include two or more folding robots 7000 to prevent a process bottleneck at the folding step. Additionally, two or more of the robots can be combined in a single module in alternate implementations. In implementations, one or more of the robots in the process line 100 are configured to communicate over wired connections or wireless communication protocols. For example, in implementations, one or more robots in the process line 100 can communicate with another one or more robots in the process line 100 over a wired BUS, LAN, WLAN, 4G, 5G, LTE, Ethernet, BLUETOOTH, or other IEEE 801.11 standard.

Referring to FIG. 2, an example of a system 200 of operatively connected autonomous robots is shown. FIG. 2 depicts a schematic implementation of a portion of an autonomous robotic process line 100 that processes the clean deformable laundry articles. A folding robot 7000 is in operative communication with a repositioning robot 6000 configured to output a repositioned, or substantially spread, deformable laundry article to the folding robot 7000, and the folding robot is in communication with a packing robot 8000 configured to receive the folded article for packing for return to the customer. In implementations, each robot 6000, 7000, 8000 includes at least one controller 6005, 7005, 8005 configured to operate the associated robot.

For example, in implementations, the folding robot 7000 includes a controller 7005. The controller 7005 includes a

16

processor 7015 in communication with a memory 7010, a network interface 7020, and a sensor interface 7025. The processor 7015 can be a single microprocessor, multiple microprocessors, a many-core processor, a microcontroller, and/or any other general purpose computing system that can be configured by software and/or firmware. In implementations, the memory 7010 contains any of a variety of software applications, algorithms, data structures, files and/or databases as appropriate to the requirements of repositioning non-uniform deformable laundry articles. In one implementation, the controller 7005 includes dedicated hardware, such as single-board computers, one or more GPUs, application specific integrated circuits (ASICs), and field programmable gate arrays (FPGAs).

A network interface 7020 is configured to couple the controller 7005 to a network 230. The network 230 may include both private networks, such as local area networks, and public networks, such as the Internet. It should be noted that, in some examples, the network 230 may include one or more intermediate devices involved in the routing of packets from one endpoint to another. In implementations, the network interface 7020 is coupled to the network 230 via a networking device, such as a bridge, router, or hub. In other implementations, the network 230 may involve only two endpoints that each have a network connection directly with the other. In implementations, the network interface 7020 supports a variety of standards and protocols, examples of which include USB (via, for example, a dongle to a computer), TCP/IP, Ethernet, Wireless Ethernet, BLUETOOTH, ZigBee, M-Bus, CAN-bus, IP, IPV6, UDP, DTN, HTTP, FTP, SNMP, CDMA, NMEA and GSM. To ensure data transfer is secure, in some examples, the controller 7005 can transmit data via the network interface 7020 using a variety of security measures including, for example, TLS, SSL or VPN. In implementations, the network interface 7020 includes both a physical interface configured for wireless communication and a physical interface configured for wired communication. According to various embodiments, the network interface 7020 enables communication between the controller 7005 of the repositioning robot and at least one of the plurality of robots 2000, 3000, 4000, 5000, 6000, 8000, 9000 of the process line 100.

Additionally or alternatively, the network interface 7020 is configured to facilitate the communication of information between the processor 7020 and one or more other devices or entities over the network 230. For example, in implementations, the network interface 7020 is configured to communicate with a remote computing device such as a computing terminal 205, database 235, server 240, smartphone 245, and server farm 250. In implementations, the network interface 7020 can include communications circuitry for at least one of receiving data from a database 235 and transmitting data to a remote server 240, 250. In some implementations, the network interface 7020 can communicate with a remote server over any of the wired protocols previously described, including a WI-FI communications link based on the IEEE 802.11 standard.

In some examples in accordance with FIG. 2, the network 230 may include one or more communication networks through which the various robots and computing devices illustrated in FIG. 2 may send, receive, and/or exchange data. In various implementations, the network 230 may include a cellular communication network and/or a computer network. In some examples, the network 230 includes and supports wireless network and/or wired connections. For instance, in these examples, the network 230 may support one or more networking standards such as GSM,

17

CMDA, USB, BLUETOOTH®, CAN, ZigBee®, Wireless Ethernet, Ethernet, and TCP/IP, among others. In implementations, the network 230 can implement broadband cellular technology (e.g., 2.5 G, 2.75 G, 3 G, 4 G, 5 G cellular standards) and/or Long-Term Evolution (LTE) technology or GSM/EDGE and UMTS/HSPA technologies for high-speed wireless communication.

Although an embodiment of a controller 7005 of the folding robot 7000 is described herein in particular, one or more of the plurality of robots 2000, 3000, 4000, 5000, 6000, 8000, 9000 of the process line 100 includes similar components having similar functionality.

Turning to FIG. 3, an implementation of a schematic controls system 400 of a folding robot 7000 (also alternatively referred to hereinafter as “a robotic device,” “device,” and “folding device”) is shown. FIG. 3 depicts an implementation of concurrently monitored and/or autonomously controlled components of the folding robot 7000 in operable control with the one or more controllers 7005 of the system 400. In implementations, each of the components comprises one or more elements having similar or identical functionality to the components described with regard to FIG. 2, such as processors, sensor interfaces, and networking interfaces for communicating with a controller 7005 and other components of the system 400 via at least one of a wired and wireless network 230. The system 400 includes one or more of the features described with regard to the embodiments of FIGS. 1 and 2. In implementations the system 400 comprises a rotatable platform 7100 and at least two of the following: at least one movable sweep rod 7400, at least one clamp rod 7200, and at least one blade assembly 7600 in wired or wireless communication with the at least one controller 7005. In implementations, the system 400 comprises a transfer conveyor 6070 configured to deliver a repositioned deformable laundry article 7300 to the platform 7100 for folding. The repositioned deformable laundry article can be at least one of spread out, oriented, and partially folded by a preceding autonomous robot, for example a repositioning robot 6000 manipulating and outputting the repositioned article 7300.

Taking FIGS. 3-5 together, in implementations, the folding device 7000 includes one or more of the features described with regard to the embodiments of FIGS. 1-3. In implementations, the device 7000 comprises a rotatable platform 7100 configured to receive a deformable article thereon for folding to a packing state that is at or within the bounds of predetermined outer dimensions. The rotatable platform 7100 comprises a substantially flat, smooth surface 7105. As indicated in FIG. 4, a coordinate system can include orthogonal X-axis “Tx” and Y-axis “Ty” coordinates defined by the planar surface 7105 and a Z-axis “Tz” substantially orthogonal to the planar surface 7105 and the X-axis “Tx” and Y-axis “Ty”. In implementations, the surface 7105 is continuous. Implementations of the continuous surface 7105 can include one or more seams. Alternatively, the rotatable platform 7100 can be monolithic. In implementations, the device 7000 includes at least one clamp 7200, 7200a, 7200b configured to clamp the deformable article to the surface 7105 in a lowered position. The at least one clamp 7200, 7200a-b is configured to raise and lower from the surface 7105 of the rotatable platform and slidably move parallel to the surface 7105. In implementations, the at least one clamp 7200, 7200a, 7200b is configured to be moved in Tx, Ty, and Tz directions by drive motors in operable communication with corresponding clamp drives, e.g. X axis drive 7230, 7230a-b, Y axis drive 7235, 7235a-b, and Z axis drive 7240, 7240a-b (FIG. 3). In implementa-

18

tions, the at least one clamp 7200, 7200a-b can be an elongated rod. In other implementations, the at least one clamp 7200, 7200a-b can be an elongated flat, spatula-like bar. In implementations, the at least one clamp 7200 can comprise two retractable clamps 7200a, 7200b as shown in FIGS. 4 and 5, configured to be simultaneously controlled for synchronized, coordinated movement.

As shown in FIGS. 6 and 7, the device 7000 includes a table drive motor 7110 configured to engage the rotatable platform 7100 and rotate the platform 7100 about a central axis. The table drive motor 7110 is driven by a motor drive 7130 (FIG. 3) in operable communication with the controller 7005. In implementations, the table drive motor 7110 comprises a driven friction wheel 7112 configured to engage a table drive ring 7115 centered about a central axis oriented in the direction of the Z-axis Tz and through a center 7107 of the platform 7100 as shown in FIG. 4. The table drive motor 7110 can include an encoder 7145 for determining rotational position of the rotatable platform 7100. In implementations, the rotatable platform 7100 is at least one of belt driven and chain driven and comprises a central shaft about which the platform 7100 rotates. The central shaft comprises at least one shaft encoder 7155 for determining a rotational position of the rotatable platform. The controller 7005 is configured to receive signals from at least one of the encoder 7154, 7155 and a positional feedback sensor (e.g., an optical sensor 7160 such as a break beam or a camera configured to detect one or more detectable fiducials, a hall sensor, etc.) for determining the rotational position such that an article on the platform 7100 can be rotated to a particular angle for at least one of clamping and folding, as will be described subsequently with regard to implementations. In implementations, the one or more encoders 7145, 7155 and sensors 7160 are in communication with a sensor interface 7140 configured to communicate with the controller 7005 via a network interface. Additionally or alternatively, the platform 7100 comprises a processor 7125 in operable communication with the motor drive 7130, the encoder 7145, 7155, one or more sensors 7160, the sensor interface 7140, and the network interface 7135 configured to communicate with the controller 7005 via wired or wireless communications.

As shown in FIG. 8, the rotatable platform 7100 can be oriented like a compass with “North” N, indicating a beginning for rotation, regardless of the position of the turntable as determined by encoder ticks. The encoder tic position can inform a direction of travel (e.g., rotation) to arrive at a desired rotational position. In one implementation, a full rotation comprises 4096 ticks. The number of ticks in a full rotation can be specific to a particular encoder. As shown in FIG. 8, the rotatable platform 7100 can be round and a complete rotation of the rotatable platform 7100 includes rotating a north most point 7120 by 360 degrees, or, 4096 ticks. For example, as shown in FIG. 9A a deformable article 7300 can be disposed on the rotatable platform 7100 such that a clothing vector 7302 is at an initial angle α_1 to a radius 7303 through the northern most point 7120. As shown in FIG. 9A, rotating the platform 7100 counterclockwise until to a desired rotational position results in an angle α_2 between the clothing vector 7302 and the radius through the northern most point 7120. The desired angle α_2 can be selected to align the clothing vector and/or a fold line 7305 with a clamp rod 7200 as will be described subsequently with regard to implementations. As shown in FIGS. 6 and 7, the table drive motor 7110 can rotate the rotatable platform 7100 such that the at least one clamp rod 7200, 7200a-b aligns with a first clamp position 7305 on the deformable article 7300. The first clamp position 7305 can be, for

example, a fold line on the deformable article **7300**, along which at least a portion of the article **7300** is folded.

As shown in FIGS. **4-5** and **10A-B**, the device **7000** also includes at least one movable sweep rod **7400** disposed parallel to the at least one clamp rod **7200**, **7200a-b**. In implementations, the at least one movable sweep rod **7400** is configured to be moved in at least Tx and Tz directions (e.g., in the direction of double arrows SA and SB) by drive motors in operable communication with corresponding sweep drives, e.g., X axis drive **7430**, **7430a-b** and Z axis drive **7440**, **7440a-b**. Optionally, in some embodiments, the at least one movable sweep rod **7400** is configured to be moved in the Ty direction by at least one drive motor in operable communication with at least one Y axis drive. Additionally, in implementations, the at least one movable sweep rod **7400** is configured to be rotate about its longitudinal axis by a rotation motor in operable communication with a spin drive **7435**, **7435a-b**. As indicated in FIGS. **10A-B**, the at least one Z-axis drive **7440** is configured to raise and lower the at least one movable sweep rod **7400** from the surface **7105** of the rotatable platform **7100**, in the direction of bidirectional arrow SA. The at least one movable sweep rod **7400** is configured to slidably move parallel to the surface in the direction of bidirectional arrow SB, which aligns with an X-Axis coordinate "Tx" of the device **7000**, alternatively referred to in implementations as a West "W" to East "E" axis.

As shown in FIGS. **11A-13**, under the operable control of the at least one controller **7005**, the at least one movable sweep rod **7400** is configured to slide under an unclamped portion **7310** of the deformable article **7300**, and lift the unclamped **7310** portion above the at least one clamp rod **7200**. For example, as shown in FIG. **11B**, the at least one movable sweep rod **7400** is configured lift the unclamped portion **7310a** of the deformable article **7300** to a height of Lz above the surface **7105** of the rotatable platform **7100** while the at least one clamp rod **7200** is clamped to the surface **7105** at the first clamp position **7305**. As shown in FIGS. **12** and **13**, the at least one movable sweep rod **7400** is configured to pass, or carry, the unclamped portion **7310a** over the at least one retractable clamp rod **7200**, and dispose the lifted unclamped portion **7310a** to a resting position atop another portion **7310b** of the deformable article **7300** while continuing to move in the X-axis direction Tx (East to West in FIG. **13**) to disengage from the article. As depicted in FIG. **12**, in implementations, the at least one movable sweep rod **7400** can move in an arc **7410** while passing the unclamped portion **7310a** deformable article **7300** over the at least one clamp rod **7200** at a peak height ZMax above the surface **7105** of the platform that clears the clamp rod and enables the article to wrap around the clamp rod. In implementation, the article wraps around the clamp rod **7200** in tension during folding for a tightest possible fold bend radius that ensures a stable fold.

Carrying the unclamped portion **7310a** in an arc **7410** ensures the raised portion **7310a** of the article **7300** is passed up, over, and away from the clamp to land atop an unclamped portion **7310b** of the article disposed on the rotatable platform in as tightly folded a layering as possible, wrapping the folded unclamped portion **7310a** around the clamp rod **7200**. Laying the folded layers as flat as possible ensures the final folded garment will be stackable in a packing queue without toppling and/or unfolding. As will be described subsequently, with regard to implementations of methods of folding, at least one of article thickness and stiffness are considered in determining where to place a clamp rod **7200** such that the unclamped portion **7310a**

passed over the clamp does not resist folding and spring back to an unfolded state. In implementations, thicker and stiffer fabrics require clamping further into a garment from the edge than thinner, less stiff fabrics. In implementations, a default minimum clamp position from an edge (e.g., 5 cm, 5.5 cm, 6 cm, 6.5 cm, 7 cm, 7.5 cm, 8 cm, 8.5 cm, 9 cm, 9.5 cm, 10 cm, 10.5 cm, 11 cm, 11.5 cm, 12 cm, 12.5 cm) ensures successful folding regardless of fabric type or thickness.

As previously described, the folding device **7000** is configured to fold a plurality of types of deformable articles. In implementations, the received deformable article is substantially extended. For example, a preceding robot in the process line (e.g., a repositioning robot **6000**) can manipulate each of the deformable articles to spread each the article **7300** such that all extremities, arms, and legs are fully spread or substantially spread to a flat or substantially flat condition. A substantially flat condition can include a deformable article **7300** having in a range of 1 to 5 tucked or twisted edges or corners of the article that can be resolved and/or accommodated by smoothing and folding processes executed by the folding robot **7000**. Additionally or alternatively, in implementations, flat or substantially flat can include articles comprising a plurality of surface wrinkles that can be resolved and/or accommodated by smoothing and folding processes executed by the folding robot **7000**.

In implementations, the deformable article **7300** is one of a plurality of deformable laundry articles comprising two or more article types of at least one of different sizes and different shapes. For example, the deformable article **7300** can be one of a plurality of laundry articles comprising a single load of household laundry. Household laundry can comprise many types of bodily worn garments and cloth articles requiring washing (e.g., sheets, tablecloths, curtains, bath rugs). These garments and articles are deformable meaning they do not hold their shape. Because garments and other cloth articles are supple, they deform when manipulated. Different items of the plurality of laundry articles may have different thickness and stiffness values depending on the material and style of the item. For example, a woven bathmat will be stiffer than a silk blouse. The plurality of laundry articles in a single load of household laundry also can comprise many different laundry articles each having a different weight. Additionally, the size of each deformable article **7300** of the plurality of laundry articles can vary greatly within a single load of laundry, such that folding each deformable article **7300** requires maneuvers particular to each article. As will be described subsequently with regard to implementations, the controller **7005** will determine a folding process based on a determination of at least one of article type (e.g., shirt, pants, sock, bathrobe, zippered top, hooded sweatshirt, blouse, button front shirt, sweater, baby clothes, coats, blankets, coats, curtains, bed sheets, and towels), article size, article material thickness, material stiffness, receiving box remaining available volume, one or more predetermined target final folded area footprint dimensions, and dynamical changing responses to each sequential maneuver.

In implementations, each of the two or more article types comprises a longest dimension of between about 4 cm to 500 cm. Accordingly, in examples, the rotatable platform **7100** has a shortest dimension in a range of between about 0.5 m to 5 m. In examples, such as those of the preceding examples, the rotatable platform **7100** is circular and the shortest dimension is a diameter. In implementations, the diameter is in a range of about 2.4 m to 2.6 m. In examples, the platform comprises a continuous flat surface. The con-

tinuous flat surface **7105** can be opaque. In implementations, the continuous flat surface **7105** comprises at least one of a solid color and pattern. In implementations, the flat surface **7105** can include one or more fiducial markers affixed to the flat surface **7105** at known positions about z-axis T_z for orienting the deformable article **7300** on the rotatable platform **7100**. For example, the fiducial marker can be one or more visible markers (e.g., a line, a dot, a barcode tag, a letter, a number, a refractory disc, etc.) detectable by an optical sensor disposed adjacent the platform **7100** for sensing detectable fiducial markers on the surface **7105** of the platform **7100**. The one or more sensors can output a signal to the controller **7005**, and the controller can determine a rotational position of the platform **7100** based on the received signal indicative of a pose of one or more sensed fiducial markers relative to a known rotation position (e.g., a "home" position, such as a 0-degree rotational position). In implementations, the rotatable platform **7100** comprises a cross sectional thickness (in the direction of T_z) in a range of between about 0.5" to 2" (e.g., in a range of between about 1 cm to 5 cm). The rotatable platform **7100** comprises and/or is manufactured from at least one of foam core, polystyrene, balsa wood, aluminum, aluminum honeycomb, stainless steel, sign board, bamboo, and ULTRABOARD. The rotatable platform **7100** comprises and/or is manufactured from a stiff, lightweight material that has a low inertia under rotation for more immediate response to commands to rotate and stop in precise alignment to one or more of the clamp rod **7200**, the sweep rod **7400**, and another element, such as a folding blade **7650** as will be described subsequently with regard to implementations.

In examples, the table drive motor **7110** is configured to rotate the platform **7100** at a fastest speed in a range of between about 30 RPM to 120 RPM. The table drive motor **7110** can be reversible and configured to rotate the platform **7100** in at least one of a forward direction and reverse direction depending on the most efficient rotation (e.g., a least amount of rotational distance) for orienting a received article with the at least one clamp rod **7200**.

Returning to FIGS. **10A** and **10B**, in implementations, the folding device **7000** further comprises a first pair of parallel support rails **7420a**, **7220a** disposed adjacent the platform **7100**. The at least one clamp rod **7200** is configured to engage a first carrier **7212a** slidably disposed on an inner one **7220a** of the pair of parallel support rails and the at least one sweep rod **7400** is configured to engage a second carrier **7412a** slidably disposed on an outer one **7420a** of the parallel rails. Alternatively, the at least one clamp rod **7200** can be configured to engage the second carrier slidably disposed on the outer one of the pair of parallel support rails and the at least one sweep rod can be configured to engage the first carrier slidably disposed on the inner one of the parallel rails. As shown in FIGS. **14-15** and **18-19**, in implementations, the first and second carrier **7212a**, **7412a** each further comprise at least one of a clamp Z-axis drive motor **7205a** and a sweep Z-axis drive motor **7405a**. In implementations, the at least one Z-axis clamp drive motor **7205a** and the sweep Z-axis drive motor **7405a** are linear drive motors configured to raise and lower the engaged at least one clamp rod **7200** and at least one sweep rod **7400** up and down, away from and toward, the surface **7105** of the platform **7100** in the direction of double arrows **SA**, **CA** and **CB**. In implementations, the at least one clamp rod is a pair of clamp rods **7200a-b** that can operate synchronously or asynchronously, lowering to different clamp heights to accommodate uneven thicknesses of an article disposed on the platform **7100**.

In implementations, the linear drive motor **7205**, **7405** can operate a linear actuator **7209**, **7409** including at least one of a belt, chain and sprocket, a screw drive, and a pneumatic drive. In implementations, the folding device **7000** comprises similar components on both sides of the platform, and the Z-axis drive motors **7205a-b**, **7405a-b** on either side of the platform **7100** are configured to be synchronously controlled for level raising and lowering the engaged respective clamp rod **7400** and one or more sweep rods **7200a-b** evenly along their lengths. Alternatively, in implementations, the Z-axis drive motors **7205a-b**, **7405a-b** on either side of the platform **7100** can be asynchronously controlled, being operated one side at a time, for example, to accommodate clamping a particular article having a sensed uneven thickness (e.g., measured height from the surface **7105**) In implementations, the Z-axis drive motors **7205a**, **7405a** further comprise a motor gear brake for preventing the raised sweep rod **7400** and one or more clamp rods **7200a-b** from lowering in an uncontrolled and unexpected movement.

As shown in FIGS. **10A-B**, and **14-15** the first carrier **7212a** can be configured to cantilever the engaged at least one clamp rod **7200a** above the rotatable platform **7100**. Additionally or alternatively to the at least one clamp rod **7200**, **7200a**, **7200b** being retractable and/or telescoping, as shown in FIG. **17** the first carrier **7212a** can further comprise a pivot joint **7214a** for tilting the engaged at least one clamp rod **7200a** above the rotatable platform **7100** in the direction of arcs **CRA** and **CRB**. In examples, as shown in FIGS. **14-16A-B**, the at least one clamp rod **7200**, **7200a**, **7200b** is retractable, and the first carrier **7212a** further comprises at least one friction wheel **7213a** configured to engage the clamp rod **7200a** for extending and retracting over the platform **7100** in the direction of double arrows **RA** and **RB**. For example, the at least one friction wheel **7213a** is driven by a Y-axis drive motor **7207a** in operative communication via a drive belt or other similar motion transfer mechanism. The Y-axis drive motor **7207a** drives the friction wheel to rotate forward and in reverse to extend and retract the at least one clamp rod **7200a**. The friction wheel engages a lower edge of the at least one clamp rod **7200**, **7200a**, **7200b** to extend and retract the at least one clamp rod over the platform **7100** and a deformable article **7300** disposed thereon. In implementations, the at least one clamp rod **7200**, **7200a**, **7200b** can be supported by two or more rotatable guide wheels **7211a-d** for supporting and aligning the at least one clamp rod **7200**, **7200a**, **7200b** at a fixed position parallel to the y-axis T_y . In examples, the at least one clamp rod **7200**, **7200a**, **7200b** is telescoping and configured to extend and retract over the platform **7100**.

In implementations, the first and second carriers **7212a**, **7412a** are configured to transit along the first pair of parallel support rails **7420a**, **7220a** at drive rate of between about 5 mm/s to 3 m/s in either direction parallel to the X-axis T_x . In implementations, the first and second carriers **7212a**, **7412a** transit at a rate in a range of between about 5 mm/s to 0.5 m/s during a folding motion. In implementations, first and second carriers **7212a**, **7412a** transit at a rate in a range of between about 1 m/s to 3 m/s during a stowing motion that moves the at least one clamp **7200** and sweep rod **7400** aside to provide an unimpeded volume above the platform **7100** through which one or more conveyors or arms transits to retrieve the folded laundry article. As indicated in FIGS. **10A**, **15**, and **18-19**, the first and second carriers are driven to slide along the first pair of parallel support rails **7420a**, **7220a** by respective first and second X-axis drive motors **7206a**, **7406a**. In implementations, the X-axis drive motors

7206a, 7406a power linear actuators configured to move the first and second carriers **7212a, 7412a** along their respective support rails **7420a, 7220a** in the X-axis Tx direction, as indicated by double arrow SB. In implementations, the linear actuators comprise at least one of a belt, such as a timing belt **7208a-b, 7408a-b** a chain, a reel and spool, and a pneumatic drive. In implementations, each of the X-axis drive motors **7206a, 7406a** comprises a shaft encoder **7265a, 7465a**. Additionally or alternatively, each of the support rails **7420a, 7220a** comprises a limit switch **7270, 7470** for determining a starting, or home, position of each respective carrier **7212a, 7412a** and an incremental position encoder **7260, 7460** for subsequently tracking a location of each carrier **7212a, 7412a** along their respective support rail **7420a, 7220a** during folding and smoothing operations.

In implementations, as shown in FIGS. 4-6 and 10A, the folding device **7000** further comprises a second pair of parallel support rails **7420b, 7220b** disposed parallel to the first pair of parallel support rails **7420a, 7220a** and adjacent the rotatable platform **7100** such that the rotatable platform **7100** is disposed between the first pair of parallel support rails **7420a, 7220a** and second pair of parallel support rails **7420b, 7220b**. The second pair of parallel support rails **7420b, 7220b** comprises a second set of carriers **7212b, 7412b** and X-axis drive motors **7206b, 7406b**, Y-axis drive motor **7207b**, and Z-axis drive motors **7205b, 7405b** as described previously with regard to the first parallel support rails **7420a, 7220a** and corresponding carriers **7212b, 7412b**, drives, linear actuators, shaft encoders, limit switches and incremental encoders. In implementations, as shown in FIG. 10B, the first and second pairs of parallel support rails **7420a-b, 722-a-b** are supported by a base such that the support rails are raised from a floor surface to a height proximate the platform **7100**. In implementations, the first pair **7420a, 7220a** and second pair **7420b, 7220b** of parallel support rails are disposed lower than the platform **7100**. Alternatively, the first pair **7420a, 7220a** and second pair **7420b, 7220b** of parallel support rails are disposed at the height of the platform **7100**.

In implementations, the X-axis drive motors **7206a-b** of the at least one clamp rod **7200, 7200a-b** are configured to be synchronously controlled on both sides of the platform **7100** to maintain the carrier ends of the at least one clamp rod **7200** at matching positions along their respective rails and therefore in line with one another along a Y-axis Ty. In implementations in which the at least one clamp rod **7200, 7200a-b** is a single rod, the synchronized control of the X-axis drive motors **7206a-b** prevents an uneven motion of the carrier ends that would result in twisting the unitary clamp rod **7200**. Similarly, the X-axis drive motors **7406a-b** of the sweep rod **7400** are configured to be synchronously controlled on both sides of the platform **7100** to maintain the carrier ends of the at least one clamp rod **7200** at matching positions along their respective rails and therefore in line with one another along a Y-axis Ty.

In implementations, as shown in FIGS. 10A, 10B, 15 and 17, the at least one clamp rod **7200** comprises a first clamp rod **7200a** engaged with the first carrier **7212a** and a second clamp rod **7200b** engaged with a third carrier **7212b** slidably engaged with one of the second pair of support rails **7420b, 7220b**. The third carrier **7212b** can be engaged with an inner one **7220b** of the second pair of parallel support rails. Alternatively, the third carrier **7212b** can be slidably engaged with an outer one **7420b** of the second pair of parallel support rails. Under operative control of the at least one controller **7005**, the X-axis drive motors **7206a-b** of the first and second clamp rods **7200a-b** can be configured to

transit synchronously the first and second clamp rods **7200a-b** along their respective support rails **7220a-b** in an X-axis Tx direction (e.g., the direction of double arrow SB). Alternatively, the first and second clamp rods **7200a-b** can be configured to slide asynchronously in an X-axis Tx direction, for example, when clamping an article in more than one location simultaneously or when clamping with only of the first and second clamp rods **7200a-b** and stowing the other out of the way of the sweep rod **7400** during a folding motion. Under operative control of the at least one controller **7005**, the Y-axis drive motors **7207a-b** of the first and second clamp rods **7200a-b** can be configured to extend and retract the first and second clamp rods **7200a-b** synchronously along the Y-axis Ty direction (e.g., the direction of double arrows RA and RB). A central longitudinal axis of each of the first and second clamp rods **7200a, 7200b** can align with a shared axis such that the rods align end to end over the platform **7100**. As shown in the magnified portion of FIG. 9A, the first and second clamp rods **7200a-b** comprise a gap DC therebetween of between about 0 to 50 mm in a fully extended position. In implementations, the first and second clamp rods **7200a-b** can extend to allow the sweep rod **7400** to pass over the first and second clamp rods **7200a-b** while moving along the X-axis Tx direction.

In implementations, the at least one clamp rod comprises a single piece clamp rod engaged with the first carrier and a third carrier slidably engaged with an inner one of the second pair of parallel support rails such that the single clamp rod extends across the entire rotatable platform. The single piece clamp rod can be retractable and the first carrier can further comprise at least one friction wheel configured to engage the clamp rod for extending and retracting over the platform. The at least one clamp rod can be telescoping and configured to extend and retract over the platform. In examples of at least one of a retractable and telescoping single clamp rod, the third carrier can be configured to selectively receive and release the single clamp rod when fully extended. In examples, the first carrier further comprises a pivot joint for tilting the engaged at least one clamp rod above the rotatable platform and the third carrier is configured to selectively receive and release the single clamp rod when tilted to a lowered position.

In implementations, the at least one sweep rod comprises a first sweep rod configured to engage with the second carrier and a second sweep rod configured to engage with a fourth carrier slidably engaged with one of the second pair of parallel support rails. In examples, the fourth carrier is slidably engaged with an outer one of the second pair of parallel support rails. In examples, the fourth carrier is slidably engaged with an inner one of the second pair of parallel support rails. In implementations, as shown in FIGS. 4-6, 10A-B, and 18-19, the at least one sweep rod **7400** comprises a single sweep rod **7400** engaged with the second carrier **7412a** slidably engaged along an outer support rail **7420a** of the first pair of parallel support rails and a fourth carrier **7412b** slidably engaged with an outer support rail **7420b** of the second pair of parallel support rails, the single sweep rod **7400** extending across the entire rotatable platform **7100**. Additionally or alternatively, the parallel support rails can comprise three or more rails on opposing sides of the platform **7100**. For example, a third rail or pair of rails (one on each side of the platform) can support one or more of a pin point clamp, a robotic arm, a rotatable blade (as will be subsequently described with regard to implementations), and a scoop conveyor for retrieving a folded article from the surface of the platform **7100**.

25

In implementations, as shown in FIGS. 18 and 19, the folding device 7000 further comprises at least one spin drive motor 7407, 7407a, 7407b operating under the control of the spin drive 7435. The spin drive motor 7407, 7407a-b is configured to rotate (e.g., spin) the at least one movable sweep rod 7400 about a longitudinal axis at least one of parallel to or coaxial with a longitudinal central axis SL of the sweep rod 7400 while suspended above the platform 7100 and slidably moving in an X-axis Tx direction along corresponding support rails 7420a-b. In implementations the at least one spin drive motor 7407, 7407a-b comprises a first spin drive motor 7407a disposed on the second carrier 7412a and a second spin drive motor 7407b disposed on the fourth carrier 7412b. Under operative control of the at least one controller 7005, the spin drive motors 7407a-b are configured to spin synchronously such that the entire length of the sweep rod 7400 rotates at the same revolution rate. In implementations, the spin drive motors 7407a-b each rotate a drive belt or other similar motion transfer mechanism to spin the sweep rod 7400. Rotating the entire length of the sweep rod 7400 at the same revolution rate and rotational position ensures that the rod 7400 does not twist or cause an article being swept smooth by the sweep rod 7400 to bunch by moving up or beneath the article at variable rates of rotation. In implementations, the spin motors 7407a-b are configured to engage a shaft encoder for maintaining a rotational position and such that a controller can monitor for any slip.

In implementations, as shown in FIGS. 20A-C, the at least one movable sweep rod 7400 is configured to slide under a terminal edge 7315 of an unclamped portion 7310a of the garment 7300 while rotating, as indicated by directional arrow 7411. As will be described subsequently with regard to implementations, one or more sensors 7160, 7160a-c (FIG. 10B) can be configured to detect the terminal edge 7315 for aligning a length of the at least one movable sweep rod 7400 with the length of the terminal edge such that the terminal edge tangentially contacts movable sweep rod upon contact. This tangential contact assists with rotating the terminal edge up and onto the rotating sweep rod 7400 so that the rotating sweep rod 7400 can slide beneath the article 7300 disposed on the platform. In implementations, at least one movable sweep rod 7400 rotates under the deformable article 7300 clockwise while sliding from the right of the at least one clamp rod 7200, 7200a-b to the left in the direction of arrow F1 and counterclockwise while sliding from the left of the at least one clamp rod to right, in the direction opposite arrow F1. In examples, the at least one movable sweep rod 7400 rotates in a range of about 5 to 500 RPM. In implementations, the at least one movable sweep rod 7400 rotates in a range of between about 100 RPM to 150 RPM.

In implementations, the at least one clamp rod 7200, 7200a-b and at least one movable sweep rod 7400 each comprise a shaped cross section. The shaped cross section comprises at least one of circular, rectangular, square, diamond, triangular, oval, pentagonal, hexagonal, spline, and octagonal. In examples, the shaped cross section comprises a largest dimension of between about 2 mm and 25 mm (e.g., 2 mm, 3 mm, 4 mm, 5 mm, 7 mm, 10 mm, 12 mm, 16 mm, 18 mm, 20 mm, 22 mm, 24 mm and 25 mm). In implementations, the at least one clamp rod 7200, 7200a-b and the at least one movable sweep rod 7400 each comprise a length of between about 1 m to 2.5 m. In implementations, a ratio of the length largest cross-sectional dimension comprises a range of between about 1000 to 1 to 2400 to 1. In one

26

implementation, the at least one clamp rod 7200, 7200a-b comprise a square cross section comprising a height of around about 6 mm.

As shown in FIG. 16A, in implementations, the at least one clamp rod 7200 can be diamond shaped and oriented such that a lowest point P of the diamond is configured to contact the deformable article 7300, and the at least one movable sweep rod 7400 can be circular. In implementations, as depicted in the end view of FIG. 16A, the two or more rotatable guide wheels 7211a-d comprise v-groove bearings configured to engage the pointed edges of the diamond shaped clamp rod 7200. Additionally or alternatively, in implementations, the two or more rotatable guide wheels 7211a-d comprise one or more crowned rollers having rounded edges to guarantee no wear on an engaged clamp rod 7200. By orienting the diamond shaped clamp rod 7200 point down, the at least one movable sweep rod is able to slide close to the clamp rod 7200 and form a tighter arc 7410 while lifting the deformable article 7300 over the clamp rod 7200 such that a tight fold is achieved. In implementations, the minimum distance D between the clamp and sweep rods is in a range of between 2 mm and 15 mm. In other implementations, as shown in FIG. 16B, the at least one clamp rod 7200' comprises a square cross section oriented such that a flat surface of the square contacts the deformable article for increased surface contact and application of downward clamping force and the two or more rotatable guide wheels 7211a'-d' comprise flat (e.g., smooth, constant radius) surfaces for engaging and pushing the contact surfaces of the clamp rod 7200 during extending and retracting motions.

In implementations, the at least one clamp rod 7200 and at least one movable sweep rod 7400 each comprise, or are manufactured from, at least one of wood, stainless steel, aluminum, DELRIN, polycarbonate, graphite, titanium, PVC, bamboo, and chromoly. In implementations, the rods 7200, 7400 are stiff and resistant to bending in a fully extended position. In some examples the at least one clamp rod 7200 and at least one movable sweep rod 7400 can be tubular to reduce weight while maintaining radial strength and stiffness along the length of the elongated rods. Additionally or alternatively, in implementations, the at least one movable sweep rod 7400 comprises a tensioned wire.

In implementations, the folding device 7000 further comprises one or more force sensors disposed on at least one of the at least one clamp Z-axis drive motor 7205 and a contact surface of the at least one clamp rod 7200, 7200a-b configured to contact an article 7300 disposed on the platform 7100. The one or more force sensors are configured to be in operative communication with a sensor interface 7255 and the controller 7005 via a network interface 7250 as shown in FIG. 3. The one or more force sensors can output a signal to the controller 7002 for limiting the applied clamping force to a range of between about 2.5 N and 50 N.

In implementations, as shown in FIGS. 62-64, additionally or alternatively to the sweep rod 7400, the device 7000 comprises a blade assembly 7600. The elements described herein with regard to one end of the blade assembly 7600 are generally the same on both ends of the blade assembly 7600. In implementations, the blade assembly 7600 is configured to engage with a pair of parallel support rails 7620a, 7620b, Z-axis drive motors 7605a, 7605b, X-axis drive motors 7606a, 7606b, and carriers 7612a, 7612b. The carriers 7612a, 7612b are slidably disposed on the support rails 7620a, 7620b and support the blade assembly 7600 configured to be disposed thereon. The z-axis drive motors 7605a, 7605b are configured to raise and lower the blade assembly

7600 and the X-axis drive motors are configured to move the blade assembly 7600 along the parallel support rails 7620a, 7620b. In implementations, the Z-axis drive motors 7605a, 7605b can operate a linear actuator 7609a-b (FIG. 67) including at least one of a belt, chain and sprocket, a screw drive, and a pneumatic drive. Accordingly, in implementations, the blade assembly 7600 may be moved by the X-axis drive motors 7606a, 7606b and Z-axis drive motors 7605a-b analogous to the operations as described herein with respect to the sweep rod 7400.

Taking FIGS. 63 and 65-67 together, the blade assembly 7600 comprises a blade 7650, blade side carriers 7652a-b, a blade support beam 7660, and synchronously driven rotational drive motors 7670a-b configured to change the angular position of the blade relative to the surface 7105 of the platform 7100 as will be described subsequently with regard to implementations. In implementations, each end of the blade 7650 is operably coupled to one of the rotational drive motors 7670a-b. Each of the rotational drive motors 7670a-b is operably coupled to a pair of drive sprockets 7673a-b, 7674a-b connected by a sprocket chain 7675a-b configured to transfer rotational force from the drive motor 7670. The rotational force is transferred via a drive shaft 7676a-b coupled to one of the drive sprockets 7674a-b at one end and affixed to the blade 7650 at the other end. In implementations, the drive shaft 7676a-b is affixed to the blade with at least one of a keyed surface feature and one or more set screws. In implementations, the drive shafts 7676a-b are configured to be coaxial so that when rotated synchronously, the blade 7650 rotates evenly along its length without twisting.

As depicted in FIG. 66, in implementations, the blade assembly 7600 further comprises an edge sprocket 7678a-b and a center sprocket 7679a-b. Each of the edge sprockets 7678a-b is affixed to a corresponding drive shaft housing 7677a-b of the blade assembly 7600, and each one of the drive shaft housings 7677a-b is configured to fixedly engage with corresponding carrier 7612a-b. Each rotating drive shaft 7676a-b is supported by a bearing 7684a-b engaged within the edge sprocket 7678a-b, and each of the bearings 7684a-b is configured to receive the corresponding drive shaft 7676a-b therein such that the drive shaft is configured to rotate (e.g., spin) within the bearing.

Each edge sprocket 7678a-b is configured to be operably connected to a counter rotating center sprocket 7679a-b by a corresponding sprocket chain 7680a-b such that the blade support beam 7660 is maintained in an upright position as the drive shaft 7676a-b rotates the blade, as will be described subsequently with regard to implementations. The counter rotating center sprockets 7679a-b are configured to be affixed to corresponding legs 7664, 7665 of the blade support beam 7660. As shown in FIGS. 66, each counter rotating center sprocket 7679a-b comprises a central bearing 7685a-b therein for receiving a counter rotation shaft 7682a, 7682b. Each of the counter rotation shafts 7682a-b is configured to rotate freely (e.g., spin) in its corresponding central bearing 7685a-b at one end while being affixed to the blade 7650 at the other end. The drive shafts 7676a-b cause the blade to rotate while the counter rotation shafts 7682a-b keep the blade support beam 7660 vertical. The counter rotation shafts apply a tension force through the blade 7650 to pull it straight and prevent sagging along the span.

In implementations, the counter rotation shafts 7682a-b can be attached to the blade 7650 by at least one of a threaded interface, a press fit, a keyed interface, one or more set screws, and one or more pins. In implementations the counter rotation shafts 7682a-b are affixed to the blade side

carriers 7652a-b on their respective ends of the blade for securely engaging with the thin blade at a thicker attachment portion. Additionally or alternatively, the blade side carriers 7652a-b further comprise attachment blocks 7689a-b for securely affixing the counter rotation shafts to the blade 7650 and/or blade side carriers 7652a-b. In implementations, the blade side carriers 7652a-b are blocks of metal (e.g., aluminum, stainless steel) configured to withstand constant stress, strain, and torsional force without flexing or deformably yielding. In implementations, the blade side carriers 7652a-b are affixed at both ends of the blade and are at least one of welded, riveted, screwed, glued, pressfit and pinned securely across the width of the blade 7650 so that tension forces and rotational forces transfer evenly from front-to-back and side-to-side along the blade. Additionally, the blade assembly 7600 comprises at least one load cell 7690b for measuring a tension force applied by the counter rotation shafts 7682 through the length of the blade LB (FIG. 64). In implementations, the tension force can be in a range of between about 175 lbf to 215 lbf. Additionally, in implementations, the load cell 7690b is configured to receive therein a bearing 7692b supporting the end of the counter rotation shaft 7682b such that the shaft rotates on the bearing 7692b. In implementations, the blade side carriers 7652a-b distribute the tension forces evenly from front-to-back across the plane of the blade 7650.

In the position shown in FIG. 65, the blade 7650 is perpendicular to the platform surface 7105 (shown in FIGS. 62-64). When the rotational drive motor 7670 drives the pair of drive sprockets 7673a-b, 7674a-b, the drive shaft rotates and causes the blade 7650 to rotate while the blade support beam 7660 remains vertically upright but is pushed out to one side or another of the drive shaft housings 7677a-b. Concurrently, the counter rotation shafts 7682a-b move through an arc above the drive shaft housings 7677a-b (e.g., vertically upright blade “home” position (FIG. 65), aside the drive shaft housings 7677a-b (horizontally rotated blade (FIG. 67)), and below the drive shaft housings 7677a-b (e.g., rotated past horizontal (FIG. 68)). In implementations, the blade assembly 7600 comprises one or more position sensors for detecting a position of the blade support beam 7660 relative to the drive shaft housings 7677a-b. In implementations, as shown in FIG. 66 for example, one or more sensors (e.g., a limit switch 7698, a Hall sensors) can be mounted to one or more brackets 7698b on outside surfaces of the drive shaft housings 7677a-b for detecting one or more magnets 7694b, 7696b mounted in a plurality of positions along each of the two corresponding legs 7664, 7665 to detect the position of the blade support beam. In implementations, the one or more sensors are configured to detect a starting, or home, position of the blade 7650 and blade support beam 7660. Additionally or alternatively, in implementations, rotational positions of the blade 7650 and blade support beam 7660 are tracked by a motor encoder (e.g., shaft encoder 7696 of FIG. 3) operably mounted to the rotational drive motor 7670a-b.

As shown in FIG. 67, as the blade rotates, each edge sprocket 7678a-b and corresponding counter rotating center sprocket 7679a-b counter rotate, holding the load beam 7660 in an upright position without tipping or tilting while moving in the X-axis Tx and Z-axis Tz directions. As shown in FIG. 67, the blade 7650 rotates into a position that is at about a 5-degree angle to the platform surface 7105. As shown in FIG. 68, each of the sprocket chains 7680a-b engages the teeth of one of the affixed edge sprockets 7678a-b and a corresponding one of the central counter rotation sprockets 7679a-b and maintains the blade support

beam **7660** in its upright position as the blade **7650** rotates to about a 60-degree angle with respect to the platform surface **7105**. This approximate rotational angle may be advantageous for smoothing a deformable article when placing the blade **7650** under a clamped article as described subsequently with respect to FIGS. **71A-D** and when moving the blade **7650** along a deformable article on the platform to smooth any wrinkles and/or unfurl any folded over portions of the article prior to folding. In implementations, the blade **7650** is configured to rotate through a range of between about 0 to 345 degrees for lifting, flipping, and manipulating an article during smoothing and folding processes.

As shown in FIG. **67**, a blade support beam **7660** is illustrated as having an elongated bar **7663** and two downwardly extending bars (e.g. legs) **7664**, **7665** perpendicular to the elongated bar **7663**. The blade support beam **7660** may have any suitable configuration for stabilizing and/or tensioning the blade **7650**. For example, the blade **7650** may be a thin, substantially planar blade, and tensioning the blade **7650** within the blade support beam **7660** increases the stability and uniformity of the planar shape of the blade **7650**. The blade support beam **7660** carrying the tension load ensures that the carriers and support rails do not need to carry the tension load. The surface of the blade **7650** may be generally smooth to reduce catching on or creating friction with the deformable article. The blade **7650** may be formed of a metal (e.g., aluminum, stainless steel, chromoly), carbon fiber, stretched canvas, nylon or plastic/elastomeric material; however, any suitable material configured to be held in tension along its length may be used.

In implementations, the length of the blade **7650** is generally sufficiently long so that it extends across the platform **7100**, e.g., from 0.5 m to 5.0 m, or the blade **7650** may extend only a portion of the platform **7100**. In implementations, the blade **7650** comprises a length in a range of between about 2.5 m to 3.2 m. The width of the blade **7650** may be from 5 or 10 cm to 20 cm, 30 cm, 40 cm, 50 cm or more. In implementations, the width of the blade **7650** is between 10 cm and 50 cm wide. In implementations, the thickness of the blade **7650** can be 5 mm to 3 mm or 2 mm or 1 mm or less. The dimensions of the blade **7650** may be selected to pass under a deformable article and/or to provide smoothing motions over a top of the deformable article. Because the blade **7650** is relatively long compared to its thickness, the blade **7650** is held in tension across its length LB to prevent sagging over the platform **7100**, which would result in less effective smoothing and folding of an article thereon because not all portions of the blade **7650** would contact the article evenly. In implementations, a ratio of the blade length BL to thickness comprises a range of between about 1500 to 1 to 3000 to 1.

In implementations, the blade support beam **7660** holds the affixed blade **7650** in tension to reduce bending, warping, or other asymmetries in the blade **7650**. In implementations, the blade support beam **7660** is configured to pretension the blade in an upright position to an upwardly bowed state. An application of tension force by the counter rotation shafts **7682a-b** then pulls the blade into a straightened position across its length such that the two corresponding legs **7664**, **7665** supporting the blade support beam **7660** are positioned vertically and not splayed outward at their tops when the counter rotation shafts **7682a-b** apply a force to the blade **7650**. In implementations, the blade support beam **7660** comprises one or more pre-tensioning elements. As illustrated in FIG. **69**, in implementations, a blade support beam **7660a** comprises an elongated bar **7663a** supported by two

corresponding legs **7664a**, **7665b** each comprising a perpendicular bar. A top bar **7666a** extends upward from the elongated bar **7663** and tension rods **7667a-b** extend from the top of the top bar **7666a** to the ends of the elongated bar, pulling the ends upward in tension so that the bottom of the two corresponding legs splay outward in the absence of a tension force running down the length of the blade **7650**. The tension rods **7667a-b** thus pretension the blade **7650** and counteract the tensioning forces applied to the two corresponding legs **7664a**, **7665a** by the counter rotation shafts **7682a-b** such that the two corresponding legs remain vertical and not splayed as the blade (not shown) is tensioned by the counter rotation shafts **7682a-b**. Additionally or alternatively, in implementations, as shown in FIG. **70**, the blade support beam **7660b** comprises a horizontal top truss **7663b** preloaded in tension by the truss elements disposed therein to counteract tension forces applied through the two corresponding legs **7664b**, **7665b** into the blade (not shown) connected thereto by counter rotation shafts.

In implementations, the blade **7650** comprises a variable or tapered thickness with one tapered edge that is suited to be able to slide underneath or over a deformable article more easily due to a thin profile of the tapered edge. The edge may also be smooth to reduce snagging or catching on the deformable article. In examples, the blade **7650** may have two opposing tapered edges that are suitable to be able to slide underneath a deformable article with a thicker profile in its midsection for additional stability or a uniformly thin profile may be used throughout the blade **7650**. Although the blade **7650** is illustrated as having a rectangular shape with a uniform width, it should be understood that a variable width may also be used so that the blade **7650** can have any suitable shape, such as a curved, wing shape. As illustrated, the blade **7650** is a generally uniform, solid material; however, the blade **7650** may be formed on one or more rods or other stabilizing structure. In implementations, the blade **7650** is configured to rotate around a central axis or to rotate around an axis that is off-center and closer to one of the side edges. Additionally or alternatively to any of the implementations described, a sweep rod **7400** can move simultaneously in the X-axis Tx direction with the blade **7650**, the sweep rod **7400** rotating about its longitudinal axis and leading the blade by a distance in a range of between about 1 mm and 5 mm to lift the terminal edge of an article and allow the blade **7650** to smoothly slide therebeneath without bunching or wrinkling the article.

In all implementations herein described, the blade **7650** can be used in operations analogous to the operations as described herein with respect to the sweep rod **7400**. In examples, the blade Z-axis drive motors **7605a-b** are configured to raise and lower the blade assembly **7600** relative to the platform surface **7105** and the X-axis drive motors **7606a-b** are configured to move the blade assembly **7600** along the parallel support rails **7620a-b** in the X-axis direction Tx (FIGS. **62** and **64**). The rotational drive motors **7670a-b** are configured to rotate the blade **7650** and in implementations the rotational drive motors **7670a-b** are geared for synchronized motion. The clamp rod **7400** is parallel to the blade **7650** and is configured to raise and lower from the rotatable platform and slidably move parallel to the surface such that the clamp rod **7400** can clamp a deformable article to the surface **7105** of the platform **7100**. Similar to the sweep rod **7400**, the blade assembly **7600** is operably controlled by the controller **7005** and comprises various drives, sensors, processors, and communication electronics as depicted in FIG. **3** for controlling operations of the blade assembly **7600**.

Advantageously, the blade **7650** comprises a substantially planar top surface **7651a** (FIG. **67**) and a substantially planar bottom surface **7651b** (FIG. **68**). In examples, the blade **7650**, held with one of the planar surfaces **7651a-b** at an angle to the surface of the article during movement in the X-axis Tx direction, is configured to glide over protrusions (e.g., buttons, pockets, raised decorative embellishments) on deformable articles without catching or pulling on them. Additionally, in implementations, a top surface top surface **7651a** comprises a smooth, low friction surface for smoothing an article, and a bottom surface **7651b** can comprises a higher friction, grippy surface or adhered surface material (e.g., felt, rubber, a scored surface topography) for retaining an article prior to flipping over the clamp rod. As will be described with regard to implementations, each of the planar surfaces **7651a-b** provides a substantial contact area for lifting heavy and/or stiff articles and placing them over the clamp by rotating the blade **7650** about the drive shafts **7676a-b** as the blade lifts a portion of the article from the platform and passes over the clamp rod **7400** so the heavy and/or stiff lifted portion folds over the clamp rod. Additionally or alternatively, the blade can use inertia to fling a lifted heavy article and/or an already partially folded portion of an article over the clamp rod **7400** while moving across the platform in the X-axis Tx direction perpendicular to a length LB of the blade **7650**. Additionally, the planar surfaces **7651a-b** of the blade **7650** provide continuous contact area for engaging and unfurling folded over portions during execution of a pre-folding sweep routine such that the blade does not snag on any protruding features of the article, such as buttons or other embellishments.

Additionally, each of the planar surfaces **7651a-b** is configured to support an already folded portion of the article thereon in balance such that it does not unfold or topple during a subsequent motion such as a subsequent folding motion over the clamp rod. The blade **7650** is configured to lift an already folded portion, such as a partially folded pant leg, above a clamp rod **7200** and then rotate as the blade travels over the clamp rod **7200** to flip the already folded portion neatly down. Additionally, in implementations, the planar blade **7650** is configured to securely lift a folded article during a movement onto another surface or transport conveyor. For example, in one implementation, the planar blade **7650** is configured to slide beneath an edge of a folded garment and rotate to lift the edge off of the surface **7105** of the platform **7100** so that an extending packing retrieval conveyer can approach the article and easily slide beneath the lifted edge for receiving the article without bumping it and potentially unfolding or toppling the article during extraction.

As shown in FIG. **71A**, the blade **7650** is adjacent a deformable article **7300** on the surface **7105** of the platform **7100**, and the clamp rod **7400** defines a clamped portion **7305** and an unclamped portion **7310** of the article **7300**. As illustrated, the deformable article **7300** includes a protrusion or feature **7306**, such as a button or rivet. The controller instructs the blade **7650** to move under the unclamped portion **7310** of the deformable article **7300** towards the clamped portion **7305** in FIG. **71B**. The blade **7650** is rotated to lift a planar surface **7651** of the blade to an angle γ with the lower edge of the blade **7650** contacting the surface **7105** of the platform **7500** such that the blade **7650** is pulling the article **7300** in tension against the clamp rod **7400** in FIG. **71C**. The blade **7650**, held at this angle, is then moved away from the clamp rod **7400** in FIG. **71D** to flatten and smooth the deformable article **7300** from an underside of the article **7300** while pulling the article in tension against the clamped

portion **7305**. The angle γ can be a predetermined angle. Additionally or alternatively, in implementations, the controller **7005** is configured to receive a signal from a force sensor (e.g., a loadcell disposed on the blade **7650**) indicative of force such that the controller **7500** can adjust the angle of the blade **7650** dynamically to maintain a constant force during the sweep movement. In implementations, the underside sweep angle γ can be in a range of between about 15 to 60 degrees.

As described previously, in implementations, the blade **7650** is configured to fold one portion of the deformable article **7300** over another by operating similarly to the sweep rod **7200** as shown in FIGS. **10A-10B**, **11**, and **12**. As illustrated in FIGS. **72A-72C**, the blade **7650** is positioned under the unclamped portion **7310** in FIG. **72A**. The blade **7650** is raised to a height of Lz away from the surface **7105** of the platform **7100**. In implementations, the blade is raised by moving in an arc motion **7410a**. The blade **7650** is rotated in the direction of arc **7410b** by the drive shafts **7676a-b** (omitted for clarity) toward the clamp rod **7200** in FIG. **72B** as the blade **7650** raises the article thereon above the surface **7105** of the platform **7100**. The blade **7650** continues to move over the clamp rod **7200** and, in implementations, continues to rotate while moving in an East to West direction (E-W) to dispose the raised portion of the article **7310** over the clamp rod **7200** in FIG. **72C**. Similarly to the sweep rod **7400**, the blade **7650** can continue to move (e.g., East to West) until free from contact with the article **7300**. The blade disposes the folded portion **7310a** of the article atop another portion **7310b** of the deformable article **7300** and forms a fold line at or around the clamp **7200**. In this example operation, the blade **7650** may be used to fold one portion of a deformable article over another portion of a deformable object at a fold line defined by the clamp **7200**. This operation may be repeated with the platform **7100** optionally rotating before clamping and folding one or more times as described herein with respect to implementations of folding with the clamp rod **7200** and sweep rod **7400**.

The blade **7650** can be used with any deformable article, but is particularly useful in operations involving heavier fabrics, such as denim, to form fold lines or to reduce wrinkles and smooth deformable articles **7300** as described herein. In examples, the blade **7650** and the sweep rod **7400** are provided on the same device **7000** with an optional clamp rod **7200**. In implementations, controller selects one or both of the blade **7650** and the sweep rod **7400** to forming fold lines. In implementations, selecting one or the other of the blade **7650** or sweep rod **7400** is dependent on detected or provided characteristics of the deformable article, such as at least one of fabric type, weight, article size, and shape of the deformable article.

Additionally or alternatively to folding, the blade **7650** may be used to manipulate deformable articles using various operations. In examples, the blade **7650** is configured to sweep beneath and atop an article to remove wrinkles and unfurl folded over portions. In examples, the blade **7650** may be passed at an angle over a top of an unclamped portion of a clamped deformable article such that at least an edge of the blade **7650** contacts the deformable article to reduce folds or wrinkles in the deformable article and unfurl any folded over portions. In implementations, the topside sweep angle comprises a range of between about 5 to 90 degrees. In implementations, the top side sweep angle comprises a range of between about 15 to 45 degrees. In implementations, the top side sweep angle can be preset. Additionally or alternatively, the blade **7650** further comprises one or more feedback sensors configured to output

measurements to the controller for dynamic control. The controller thus can dynamically control the angle of the blade to ride up and over protrusions and not run into them and potentially damage the article.

In implementations, the controller determines an edge of a folded article and operably controls the blade **7650** to slide under the edge. In implementations, the blade is configured to lift the folded deformable article and maintain the folded configuration while moving the deformable article to another location.

In examples, two or more blade assemblies **7600** may be used with corresponding blades **7650**. The blades **7650** may be sized and configured for different operations or different fabrics. Moreover, the blade assembly or assemblies **7600** may be used in a device **7000** including any suitable number or configuration of clamp rods or sweep rods, or two or more blade assemblies **7600** may be used with at least one of the clamp rods and sweep rod being omitted.

As described previously, in implementation as shown in FIGS. 3 and 10B the folding device **7000** further comprises one or more sensors **7160**, **7160a-c** configured to at least one of detect one of one or more features and capture one or more images of the deformable article **7300** disposed on the rotatable platform **7100**. In implementations, one or more light sources **7170a-b** are disposed about the platform for enabling detection by the one or more sensors **7160a-c** of an article **7300** on the platform **7100**. As described previously with regard to FIG. 3 the folding device **7000** further comprises a controller **7005** in operative communication with the table drive motor **7110**, the at least one Z-axis drive motors **7205**, **7405**, the at least one Y-axis drive motors **7207a-b**, the at least one X-axis drive motors **7206**, **7406**, the at least one spin motor **7407a-b**, and the one or more sensors **7160**, **7160a-c** disposed about the surface **7105**. The one or more sensors **7160**, **7160a-c** comprise at least one of a 3-D point cloud sensor, a 2-D camera, LIDAR (Light Detection And Ranging, which can entail optical remote sensing that measures properties of scattered light to find range and/or other information of a distant target), LADAR (Laser Detection and Ranging), a sonar proximity sensor, an ultrasonic ranging sensor, a radar sensor (e.g., including Doppler radar and/or millimeter-wave radar), and a pair of stereo depth cameras. In implementations, the one or more sensors **7160**, **7160a-c** output to the controller **7005** at least one of a depth map, RGB images, and IR images. In implementations at least one of the one or more sensors **7160**, **7160a-c** comprises a REALSENSE camera configured to output any of a depth map, RGB images, and IR images. In implementations, the one or more sensors **7160**, **7160a-c** can be configured to output 3-D image data to the controller **6005**. Additionally or alternatively, in implementations, at least one of the one or more sensors **7160**, **7160a-c** can be configured to output one or more 2-D images to the controller **6005**. In implementations, each one of the one or more sensors **7160**, **7160a-c** is a camera calibrated at a fixed position and orientation relative to the platform **7100**.

In one implementation, the one or more sensors **7160**, **7160a-c** can be imaging sensors including at least one of an infrared range sensor and a volumetric point cloud sensor configured to generate range value data representative of the deformable laundry article **7300** disposed on the platform **7100**. The one or more sensors **7160**, **7160a-c** can be configured to generate presence value data representative of the deformable laundry article **7300**. In implementations, the presence value data can indicate a position and orientation of the deformable laundry article on the platform **7100**.

In implementations, the controller **7005** is further configured to determine, based on a comparison of a received output signal of the one or more sensors **7160**, **7160a-c** to data stored in a memory **7010** in communication with the controller **7005**, at least one of an article type, a front side, a back side, and an inside surface of the deformable article **7300**. In implementations, at least one of the one or more sensors **7160**, **7160a-c** can be a 2-D camera and the data associated with repositioned deformable laundry article is size invariant image data.

In implementations, the memory **7010** of the controller **7005** comprises a neural network **300**, and determining the one or more characteristics of each one of the plurality of deformable articles comprises processing the received output signal of the at least one sensor with a neural network classifier. In implementations, as shown in FIG. 21, the neural network **300** comprises a trained neural network, for example a convolutional neural network that operates quickly on 3D and/or 2D data and is configured to classify images from one or more 3D and/or 2D cameras. In an implementation, the classification comprises generating a descriptor based on the output signal of the one or more sensors **7160**, **7160a-c** and classifying, using the neural network, the output signal based on the descriptor. The neural network is configured to output a probability that the output signal corresponds to a class of the stored data indicative of one or more deformable article types that require particular folding maneuvers, for example. The classes of trained data in the neural network include data associated with many types of deformable articles. For example, as shown in FIG. 21, a neural network **300** can be trained with a set of training data **305**. After training, the neural network **300** comprises a set of weights that can be used for neural network inference to determine whether an input **330** (e.g., output signal from the one of the one or more sensors **7160**, **7160a-c**) is within one of the trained classes.

In implementations, the neural network is configured to output a probability that the output signal of the one or more sensors **7160**, **7160a-c** corresponds to a class of the stored data indicative of one or more deformable laundry article types. The classes of trained data in the neural network include data associated with many types of deformable laundry articles that require particular folding maneuvers to reach a final folded state within a footprint area, as level as possible, and without unfolding.

Additionally or alternatively, in implementations, a memory store **7010** in communication with the controller **7005** comprises a trained regressor. The controller **7005** is configured to receive an input signal of the one or more sensors **7160**, **7160a-c** and, based on an output of the trained regressor, identify a feature of one or more article types to rotate in alignment with or perpendicular to one or more clamp rods **7200**, **7200a-b**. For example, the trained regressor can identify a sagittal line of a shirt and the controller **7005** can instruct the drive motor **7110** of the platform to rotate the sagittal line in one direction or the other depending on the number of radians from a perpendicular orientation to the one or more clamp rods **7200**, **7200a-b**.

In implementations the one or more sensors **7160**, **7160a-c** comprises a REALSENSE camera, positioned above the rotatable platform **7100** and aimed at the surface **7105**. In implementations, the surface of the platform **7100** is non-speculative. In implementations, the surface **7105** is a single color, such as white or grey, for providing readily detected contrast to most deformable articles **7300**. As shown in FIGS. 10A-B, the one or more sensors **7160**, **7160a-c** is a camera positioned at a height of CZ above the

35

rotatable platform. In implementations, the one or more sensors **7160**, **7160a-c** can be positioned directly above the center **7107** of the platform **7100**. Additionally or alternatively, the one or more sensors **7160**, **7160a-c** may be offset from the center of the platform and/or angled from the vertical axis **Tz**. In all implementations, the one or more sensors **7160**, **7160a-c** are positioned at a fixed height and orientation relative to the platform **7100**.

In examples, the controller **7005** is configured to receive one or more output signals from the one or more sensors **7160**, **7160a-c**, determine, based on the received one or more output signals, at least one of an article type, size, thickness, and location of the deformable article **7300** on the platform **7100**. The controller **7005** is configured to determine based on the at least one of the determined article type, determined article size, determined article thickness, and the location, a first fold line **7320** of the deformable article, instruct a drive motor **7110** to rotate the platform **7100** to align the fold line **7320** of the deformable article with the at least one clamp rod suspended above the platform, and instruct the at least one clamp rod **7200** to lower onto the first fold line **7320**, the lowered at least one clamp rod **7200** configured to apply force and immobilize the fold line of the deformable laundry article **7300** against the surface **7105**. The controller **7005** is further configured to instruct the at least one movable sweep rod **7400** to slidably move in a first direction between the deformable article **7300** and the surface **7105** to a position adjacent and parallel to the at least one retractable clamp rod **7200**, and raise the deformable article up and over the at least one retractable clamp rod **7200**, slidably moving in the first direction at least until the article disengages from the at least one movable sweep rod. In examples, such as that described above with regard to FIGS. **9A-B** aligning the fold line (e.g., the location on the article **7300** where the clamp presses, also called the clamp position **7305**) of the deformable article **7300** with the at least one clamp rod **7200** comprises rotating the fold line to a substantially parallel position with the at least one clamp rod **7200**.

In implementations, the fold lines, such as those **7320a-k** shown in FIGS. **22A-23D** each comprise a line across at least a portion of the deformable article **7300** at which the folding device **7000** is configured to fold the deformable article. The fold line **7320** crosses two outer edges of at least a portion of the deformable article. Each article type, such as the short-sleeved shirt of FIG. **22A**, the spaghetti strap camisole of **22B**, and the pants of FIGS. **23A-D** can comprise one or more fold lines **7320** about which the clamp and sweep rods and/or sweep blade **7650** will fold the unclamped portions of the article **7300**. As will be described subsequently with regard to implementations, the one or more fold lines **7320** can be preplanned in a specific order to achieve a final folded state of the article **7300** that is at or within a predetermined footprint area for queuing and packing. For example, each of the fold lines can be folded in the direction and order of the numerically marked arrows of FIGS. **22A-B** and **23A-D**. Additionally or alternatively, in implementations each of the one or more fold lines **7320** can be selected inward from a lifted edge (e.g. perimeter edge, terminal edge) to include, at a minimum, a distance accommodating a bend radius of the fabric of the deformable article **7300** and an allowance for folding the article around the clamp rod **7400** without the folding portion springing back to an unfolded state, as will be described subsequently with regard to implementations of folding. For example, in implementations, the controller **7005** clamps at a minimum distance from an edge of an article in a range of between

36

about 1 to 5 inches (e.g., 2.54 cm to 12.7 cm) for a clamp **7400** having a height and width (measured in the fold direction, e.g., the X-axis **Tx** direction) each in a range of between about 0.25 inch to 1.5 inches (e.g., 0.6 cm to 3.81 cm).

As described previously, in examples, the at least one clamp rod **7200**, **7200a-b** is retractable and configured to extend and retract over the platform **7100**. In examples, the at least one clamp rod **7200** is telescoping. In examples, the at least one clamp rod **7200**, **7200a-b** engages a driven friction wheel configured to advance and retract the at least one clamp rod **7200**. In examples, after the article **7300** disengages from the at least one movable sweep rod **7400**, the controller **7005** is further configured to instruct the at least one clamp rod **7200**, **7200a-b** to retract until disengaged from the deformable article **7300**.

Although in the above examples and implementations, the platform **7100** is rotatable, any of the above examples and implementations can apply to an alternative embodiment in which the platform **7100** is stationary and the pairs of parallel support rails **7420a-b**, **7220a-b**, **7620a-b** are fixed to one another and configured to rotate about a fixed position and about the stationary platform. As shown in FIGS. **24A-B**, for example, the pairs of parallel support rails **7420**, **7220** can be mounted to wheels or casters **7700a-b** configured to roll within a trough **7705** anchored about the platform. The wheels **7700a-b** can be drive by one or more rail rotation drive motors **7710a-b**.

Referring now to FIG. **25**, any of the examples and implementations described previously with regard to an autonomous folding device **7000** are applicable to implementations described herein with regard to a method **1100** of autonomously folding a deformable article **7300** (e.g., also referred to herein as a “deformable laundry article”).

In implementations, the method **1100** of robotically folding is configured to be executed autonomously by the controller **7005**, and, as previously described with regard to implementations, the controller **7005** is configured to be in operative communication with the one or more sensors **7160**, **7160a-c**, the drive motor **7110** of the rotatable platform **7100**, the drive motors and position sensors of the at least one clamp **7200**, and the drive motors and position sensors of the elongated sweep rod **7400** and/or blade **7650**. In examples, the controller **7005** is configured to communicate with a network **230** via at least one of wired and wireless communication protocols. In implementations, the method **1100** further comprises receiving one or more folding instructions from a remote device in operable communication with the network **230**.

In implementations, as shown in FIG. **25**, the method **1100**, comprises iterating a folding sequence one or more times, and stopping iterating the folding sequence upon the determining the article **7300** is folded to at or within a footprint area (e.g., final folded dimensions). The folding sequence comprises receiving **S1102**, at a controller **7005**, one or more output signals from one or more sensors **7160**, **7160a-c** in communication with the controller, the one or more sensors being configured to at least one of detect one of one or more features and capture one or more images of a deformable article **7300** disposed on a platform **7100**. As described previously with regard to implementations, such as that of FIG. **10B**, the one or more sensors **7160**, **7160a-c** comprise one or more cameras. In implementations, each camera **7160** is disposed at a fixed position relative to the platform **7100**. In implementations the one or more sensors **7160** comprise a single camera **7160a** affixed to a support at a central position suspended above the platform **7100** and

having a field of view **7161a** encapsulating the entire surface **7105** of the platform **7100**. Additionally or alternatively, the one or more sensors **7160**, **7160a-c** can comprise a camera **7160b** affixed to a support above and aside the platform and having an angled field of view **7161b** relative to the Z-axis **Tz** direction. Additionally or alternatively, the one or more sensors **7160**, **7160a-c** can comprise a camera **7160c** affixed to a support aside the platform and having an field of view **7161c** having a central focal point that is approximately perpendicular to the Z-axis **Tz** direction such that the camera **7160c** can detect a prominence indicative of an article thickness on the surface **7105** of the platform **7100**.

In implementations, the folding robot **7000** is configured to fold a plurality of article types and article sizes received in any unpredictable order. The folding robot executes the method **1100** regardless of article type and processes signals and data transmitting from at least one of the one or more sensors **7160**, **7160a-c** and a preceding robotic device, e.g., a repositioning robot **6000**, to determine which folding routines to execute.

As described previously, the one or more sensors **7160**, **7160a-c** comprise at least one of a 3-D point cloud sensor, a 2-D camera, LIDAR (Light Detection And Ranging, which can entail optical remote sensing that measures properties of scattered light to find range and/or other information of a distant target), LADAR (Laser Detection and Ranging), a sonar proximity sensor, an ultrasonic ranging sensor, a radar sensor (e.g., including Doppler radar and/or millimeter-wave radar), and a pair of stereo depth cameras. In implementations, the one or more sensors **7160**, **7160a-c** output to the controller **7005** at least one of a depth map, RGB images, and IR images. In implementations at least one of the one or more sensors **7160**, **7160a-c** comprises a REALSENSE camera configured to output any of a depth map, RGB images, and IR images. In implementations, the one or more sensors **7160**, **7160a-c** can be configured to output 3-D image data to the controller **6005**. Additionally or alternatively, in implementations, at least one of the one or more sensors **7160**, **7160a-c** can be configured to output one or more 2-D images to the controller **6005**. In implementations, each one of the one or more sensors **7160**, **7160a-c** is a camera calibrated at a fixed position and orientation relative to the platform **7100**.

In one implementation, the one or more sensors **7160**, **7160a-c** can be imaging sensors including at least one of an infrared range sensor and a volumetric point cloud sensor configured to generate range value data representative of the deformable laundry article **7300** disposed on the platform **7100**. The one or more sensors **7160**, **7160a-c** can be configured to generate presence value data representative of the deformable laundry article **7300**. In implementations, the presence value data can indicate a position and orientation of the deformable laundry article on the platform **7100**. In implementations the one or more sensors **7160**, **7160a-c** comprises a REALSENSE camera, positioned above the rotatable platform **7100** and having a field of view aimed at the surface **7105**.

The method determines **51104**, based on the at least one of one or more features and one or more images output from the one or more sensors **7160**, **7160a-c**, at least one of an article type, size, thickness, and a location and orientation (e.g., pose) of the footprint area of the deformable article **7300** on the platform **7100** and awaiting folding. In implementations, the controller **7005** is configured to generate a pixel map, such as the black and white map of FIG. 26, of where the article **7300** is and where it isn't on the platform **7100**. For example, in implementations, the pixel map can

determine, as indicated in white, which pixels represent a portion of the article **7300** and in back which pixels represent the surface **7105** of the platform **7100**. Determining where the garment **7300** is on the platform **7100** enables the controller **7005** to determine how far into the garment pixels to place the one or more clamp rods **7200**, **7200a-b** and how far in the X-axis direction **Tx** to move the at least one of the sweep rod **7400** and sweep blade **7650** to start the folding process.

Additionally or alternatively, the controller **7005** can identify and predict a thickness of the article **7300**. In implementations, the controller **7005** generates a depth map from a point cloud detected by the one or more sensors **7160**, **7160a-c** disposed above or adjacent the platform, and determined based on the depth map the height of the article **7300** off the surface of the platform **7100**. Additionally or alternatively, the one or more sensors can comprise one or more depth sensing devices (e.g., a 3-D stereo depth camera, a side long 2-D camera, LIDAR, etc.). This article height detection from the platform surface **7105** enables the controller **7500** to determine how deep to clamp the article **7300** down onto the surface **7105** (e.g., in the Z-axis direction **Tz**) with the at least one clamp rod **7200** and how far off the surface to position at least one of the sweep rod **7400** and blade **7650** to lightly graze a top surface of the article **7300** while passing over it in the X-axis direction.

The controller **7005** thus need not know exactly article type, size, and thickness characteristics in advent. As will be described subsequently with regard to implementations, the folding robot **7000** is configured to accommodate a plurality of disparate article types and sizes presented sequentially within a load of laundry without requiring human intervention, resetting mechanical fixtures on the robot **7000**, and or having to aim the article in a particular orientation when introduced onto the platform **7100**. The rotating platform **7100** aligns any article disposed thereon with the sweep rod **7400** and at least one of the at least one clamp rod **7200**, **7200a-b** and sweep blade **7650** regardless of size, thickness, and article type. In implementations, as will be described subsequently, the controller **7005** can select a folding routine for an article **7300** that will be ensure an efficient, stable, and visually appealing fold to a desired target footprint area for packing and return to a customer.

Returning to the method **1100** of folding, before selecting a folding routine, the method comprises determining **S1106** whether the article **7300** will fold to one of a plurality of target final footprint area dimensions or whether the article **7300** cannot be folded. For example, the controller **7005** can determine based on the at least one of the pixel map and depth map that the article is at least one of too small and too thick to fold. Additionally or alternatively, the controller can determine that the article **7300** is not sufficiently repositioned, perhaps too twisted or entangled with itself to fold. In implementations, if the article **7300** is not sufficiently repositioned, the controller **7005** can instruct the folding device or another device in the process line **100** to return the article **7300** to the repositioning robot **6000** for another attempt at repositioning. In implementations, if the controller **7005** has failed to determine the article **7300** is foldable after two or more passes through the repositioning robot **6000** or has determined the article **7300** is too small for folding, the controller **7005** is configured to send the article **7300** to the packing robot **9000** without being folded by the folding robot **7000**. Alternatively, the folding robot can attempt to fold the article **7300** in accordance with a general fold algorithm as will be described subsequently with regard to implementation. For example, the folding robot **7000** can

fold a pair of pants with one leg inside out in accordance with one or more general folding routines. Although not ideal, the final result will be an article folded to at or within a target area for proper stacking and packing without a customer return box.

If the repositioned article **7300** received on the platform can be folded, the method **1100** comprises selecting **S1110** a folding and/or smoothing routine based on targeted final folded dimensions and the determined at least one of an article type, size, thickness, and a location and orientation of the footprint area of the deformable article **7300**.

In implementations, the targeted final folded dimension comprises at least one final folded dimension that is dynamically determined. In implementations, the controller **7005** determines the at least one final folded dimension of the article **7300** based on receiving a communication from the packing robot **8000** indicative of a remaining volume in a packing container configured to receive the folded article. Additionally or alternatively, in implementations the controller **7005** is configured to select the at least one final folded dimension of the article from a plurality of target dimensions stored in a database including a plurality of target folded dimensions associated with at least two of article type, article size, article thickness, and container dimensions.

As shown in FIGS. **27A-B**, the one or more final folded dimensions can be one or more of the volumetric envelope dimensions of the folded article. The one or more volumetric envelope dimensions can be, for example a predetermined target rectangle size (WT×LT) associated with at least one of article type, article size, and article thickness, or predetermined volumetric dimensions (WT×LT×HT) associated with at least one of the article type, article size, and article thickness. In implementations, the predetermined target rectangle size is selected based on at least two of the article type, article size, and article thickness. In implementations, the controller can dynamically change the target rectangle size based on variations and article behaviors and partially folded states during the folding process.

For example, in implementations, the plurality of predetermined rectangle sizes can include folded length and width dimensions of 10×12 inches, 5×12 inches, 6×10 inches, and 5×6 inches for combining and orienting folded articles in even stacks in a particular order for efficiently loading into a shipping container **7800** having storage volume dimensions of approximately 14×24 inches. The predetermined one or more dimensions can inform the location and orientation of one or more fold lines across the article **7300** and the sequence of folds at the one or more fold lines. In some examples, an article type may be unknown or unidentifiable, and the article may be folded according to size remaining in a packing box **7800** configured to receive a plurality of folded articles **7805a-n**. For example, in implementations, an unoccupied volume **7810** determines the maximum envelope size of the final folded article for including within the box **7800**, and the controller can select a sequence of folds until the article height, width, and length fit with the volume **7810**.

Additionally or alternatively, in implementations, the controller is configured to dynamically determine the position and orientation of a fold line at which to clamp and fold an article based on at least one of the accrued number of folds already executed (if any) and a difference in a maximum height and a minimum height of a top surface of the article from the surface **7105** of the platform **7500**. The maximum and minimum height can be measured by the one or more sensors **7160**, **7160a-b** and the controller can compare the

difference to a threshold indicative of a maximum allowable slope, or lean, of the top of the folded article. For example, the threshold can be in a range of between about 1 to 3 inches (e.g., 25 mm to 75 mm) such that the folded article can be stacked with other folded articles in a stable stack in a packing queue and/or packing container without toppling. Additionally or alternatively, the controller is configured to detect a slope of the top surface based on the output signal of the one or more sensors **7160**, **7160a-b** and compare an angle of the slope relative to the horizontal plane of the platform surface **7105** to a threshold angle. For example, the threshold angle indicative of an acceptable top surface slope can be in a range of between about 0 to 30 degrees. In implementations a threshold maximum allowable tilt angle for the top surface that ensures stable stacking of two or more articles is around about 15 to 20 degrees.

Returning to the method **1100** of folding, in implementations, selecting **S1110** a folding and/or smoothing routine comprises determining **S1112** whether the article **7300** requires a specific article type fold, such as one of a plurality of specific routines **S1114** executable by the controller **7005** operably communicating with the at least one clamp rod **7200**, **7200a-b** and at least one of the sweep rod **7400** and the sweep blade **7650**. Additionally or alternatively, the method **1100** comprises determining **S1112** whether the article **7300** requires executing a general article fold routine, such as one of a plurality of general routines **S1116** executable by the controller **7005** operably communicating with the clamp rod and at least one of the sweep rod **7400** and sweep blade **7650** to fold any article in accordance with a generalized folding routine applicable to all article types, sizes, and thicknesses. The specific routines **S1114** and general routines **S1116** will be described subsequently with regard to implementations.

Once the folding routine is selected from a plurality of specific folding routines **S1114** and general folding routines **S1116**, the method comprises determining **S1117** whether the article **7300** requires smoothing by executing a smoothing routine **1200** (e.g., an algorithm with executable instructions). In other implementations, the method **1100** comprises executing a smoothing routine **1200** by default. If no smoothing is required, the method **1100** proceeds to executing the selected folding routine as will be described subsequently with regard to implementations. Each of the routines comprises one or more iterations of folding **S1132** the article over the clamp rod **7400** to achieve final dimensions at or within a pre-selected targeted final footprint area. The iterations of folding comprise determining **S1118** a clamp line of the deformable article, determining **S1120** whether the platform **7100** requires rotating to align a fold line **7320** of the deformable article with a clamp suspended about the platform, instructing **S1122** a drive motor **7110** to rotate the platform **7100** to align the fold line **7320** of the deformable article **7300** with the at least one clamp rod **7200**, **7200a-b** suspended above and elongated parallel to a surface of the platform **7100**, instructing **S1124** the at least one clamp rod **7200**, **7200a-b** to lower onto the fold line, the lowered clamp rod being configured to apply force and immobilize the fold line of the deformable article **7300** against the surface **7105** of the platform **7100**, and instructing at least one of an elongated sweep rod **7400** and a sweep blade **7650** to move. Instructing the at least one of an elongated sweep rod **7400** and sweep blade **7650** to move comprises instructing **S1130** the at least one of the elongated sweep rod and sweep blade **7650** to at least one of smooth the article, and lift and fold the article **7300** as described previously with regard to implementations of the sweep rod **7400** and blade **7650**.

41

In implementations, the fold line **7320** (e.g., fold lines **7320a-k** described with regard to FIGS. **22A-23D**), comprises a corresponding line across at least a portion of the deformable article about which the deformable article is configured to fold. In examples, the fold line crosses two outer edges of at least a portion of the deformable article **7300**.

In implementations, the drive motor **7110** is configured to operate bi-directionally and wherein instructing the drive motor to rotate the platform **7100** comprises rotating the platform **7100** at least one of in a forward direction and in a reverse direction.

Additionally or alternatively, in implementations, the method further comprises receiving input from a force sensor in operable communication with the at least one clamp drive configured to limit the applied clamping force to a range of between about 2.5 N and 50 N.

Additionally or alternatively, in implementations, the method further comprises receiving an output signal comprising a 3-D image data of the deformable article and determining, based on the 3-D image data, one or more critical features of the deformable article. In implementations, the one or more critical features comprises a portion of the deformable article comprising at least one of a raised prominence, a closure, and an affixed embellishment.

Additionally or alternatively, in implementations, determining the fold line comprises, based on the output signal of each of the one or more sensors, determining one or more natural fold lines of the deformable article. In implementations, the one or more natural fold lines comprises a bisector of the deformable article.

Additionally or alternatively, in implementations, the one or more natural fold lines comprises a seam of the deformable article.

In implementations, as will be described subsequently with regard to implementations of general and specific folding routines, the controller **7005** is configured to determine one or more fold lines **7320** based on at least one of the article type, the article size, and the article thickness. Additionally or alternatively, the controller **7005** is configured to determine the at least one targeted final folded dimension of the article by identifying in a memory store one or more predetermined final folded dimensions associated with the determined at least one of the article type, the article size, and the article thickness. Determining one or more fold lines can be based at least in part on selecting the one or more predetermined final folded dimensions and adjusting fold line location based on thickness as will be described subsequently with regard to a bend allowance.

As previously described, in implementations, the method **1100** comprises determining **S1117** whether the article **7300** requires smoothing. In other implementations, the method **1100** comprises executing a smoothing routine **1200** by default. If no smoothing is required, the method proceeds to folding. If smoothing is required, the controller **7005** is configured to execute a smoothing routine **1200**, as shown in FIG. **30**.

In some examples, an article may require only smoothing and not folding, such a small, wrinkled article, like a sock. In such examples, the device **7000** will smooth the article, and the controller **7005** will signal completion to one or more packing robots **8000** of the process line **100** for packing and returning the article to the customer.

Determining **S1117** whether an article **7300** requires smoothing comprises determining whether the entire article **7300** requires smoothing or whether only particular portions of the article require smoothing and not others. Additionally

42

or alternatively, determining **S1117** whether an article **7300** requires smoothing comprises determining whether only one of a top side smoothing pass and an underside smoothing pass is required prior to folding an article. The determining **S1117** step considers each individual article presented to the folding device **7000** and each sequentially presented article can be a unique article type, size, and thickness as is common with household laundry. Regardless of article type, size, and thickness, smoothing proceeds similarly. However, the controller **7005** can dynamically determine whether to place a clamp rod along an article bisector or closer to an edge of the article, for example based on article type, size, and thickness. Smoothing in an underside pass draws the article away from an engaged clamp rod to pull wrinkles flat. A pair of adult jeans, for example, can be clamped at the waistband and each leg can be smoothed independently.

Additionally or alternatively, smoothing outward and upward at a diagonal angle from the clamp rod can unfurl twisted protrusions and/or folded over portions of an article and particular article types, sizes, and thicknesses may benefit from the outward and upward underside smoothing, such as a pair of adult jeans. Similarly, a topside smoothing pass flattens wrinkles and unfurls folded over portions of the article. Determining whether only portions of the article require smoothing enables the controller **7005** to eliminate unnecessary, time consuming processing steps of rotating the platform **7100** and executing the smoothing routine **1200** unnecessarily. Smoothing the article flattens the article to a foldable state such that the folded article is presentably folded to a target size for efficient packing and stably folded so that the article is unlikely to unfold during subsequent maneuvers in queuing, packing, and return to a customer.

In implementations, determining **S1117** whether the article requires smoothing comprises detecting one or more wrinkles on the article **7300** disposed on the platform **7100**. In implementations, as shown in FIGS. **28-29**, identifying wrinkles comprise lighting the article from an angled source, such as the light **7170c** tilted from the Z-axis Tx and aimed at an angle to the surface of the platform **7100**. The determination then comprises detecting with the one or more sensors **7160**, **7160a-c** b, whether a shadow **7301**, **7301a-c** matches an outline of the article or falls with the edges of the article **7300**, thereby indicating a location and orientation of one or more wrinkles **7905**, **7905a-b**. In implementations, creating a shadow **7301c** about the edges of the article **7300** disposed on the platform enables the controller **7005** to match 3D sensor data of the article **7300** to the shadow **7301c**. The directional lighting creates a shadow **7301c** that enables the controller to detect the edges of the article, which is especially advantageous when color contrast between the surface **7105** of the platform **7100** and the article is low and the article is therefore difficult to perceive.

In implementations, such as that of FIG. **30**, a smoothing routine **1200** comprises a sequence of instructions that are executable by the controller **7005** and stored on a memory **7010** in communication with the controller. In implementations, as shown in the sequence of FIGS. **31A-32B** and **33A-37**, the sequence of instructions for smoothing **1200** the deformable article prior to folding comprises determining **S1202** a clamp line location (e.g. article anchor location) and orientation on the article for smoothing, determining **S1205** whether a platform rotation is needed, instructing **S1210** a drive motor **7110** to rotate the platform **7100** to align clamp line location (also herein referred to as a fold line) of the deformable article **7300** with the at least one clamp **7200**, **7200a-b** suspended above and elongated parallel to a surface **7105** of the platform **7100**. The smoothing method **1200**

comprises instructing S1215 the at least one clamp 7200, 7200a-b to lower onto the location, the lowered at least one clamp 7200, 7200a-b configured to apply force and anchor of the deformable laundry article against the surface. The smoothing method 1200 comprises instructing S1220 at least one of the elongated sweep rod 7400 and the sweep blade 7650 to slidably move in a first direction toward the at least one clamp 7200, 7200a-b to a position adjacent and parallel to the at least one clamp 7200, 7200a-b, the elongated sweep rod 7400 and/or sweep blade 7650 being disposed between the deformable article 7300 and the surface 7105 of the platform 7100. In implementations comprising a sweep rod 7400, the sweep rod is configured to rotate about a longitudinal axis while slidably moving beneath the article 7300 to prevent the article from bunching while the sweep moves in the X-axis Tx direction while in contact with the article.

In any of the preceding examples and implementations, as shown in FIGS. 31A-B and 32A-B, the sweep rod 7400 can rotate counterclockwise for the first motion comprising a right to left (east to west) movement between the article and the platform, and clockwise for the first motion comprising a left to right (west to east) movement between the article and the platform. The sweep rod 7400 can rotate clockwise for the first motion comprising a right to left movement atop the article and counterclockwise for the first motion comprising a left to right movement atop the article 7300. The direction of rotation as the sweep rod 7400 moves between the article and away from the clamp rod 7200 prevents the article thereon from bunching and pulls the fabric in the direction of movement to smooth out any wrinkles and/or folded over portions of the article. Similarly, the direction of rotation as the sweep rod 7400 moves atop the article and away from the clamp rod 7200 prevents the article thereon from bunching and pulls the fabric in the direction of movement to smooth out any wrinkles and/or folded over portions of the article. In examples, in any of the preceding examples and implementations the method further comprising repeating the sequence of instructions for smoothing, the repeated sequence comprising at least one of sliding and rotating the elongated sweep rod at a relatively slower rate than a first execution of the sequence of instructions for smoothing.

In implementations, the sweep rod 7400 rotates about its longitudinal axis. Additionally or alternatively, the sweep rod 7400, under control of the X and Z drive motors being actuated together, can sweep a circular or spiral motion as it transits underneath an article for providing addition vibration and agitation to unfurl and/or untwist folded over or twisted portions of the article.

In any of the preceding examples and implementations, the anchor location can comprise a middle location (e.g., a bisector of an article or a longitudinal axis near the bisector but offset from the bisector) of the deformable article and the sequence of instructions for smoothing the deformable article prior to folding is executed by the controller on both sides of the anchor location. In implementations, the method 1200 comprises determining S1225 whether the at least one clamp rod 7200, 7200a-b is approximately centered on the article 7300.

FIGS. 33A-33C depict an example sequence of smoothing a clamped shirt in a first orientation relative to clamp anchored at or around a bisector of the torso. The sweep rod sweeps first on one side of the clamp and then on the other. The platform rotates and, as shown in FIGS. 34A-B, the clamp anchors a middle of the rotated shirt and smooths on both sides of the clamp. FIG. 35 depicts the shirt of FIGS.

33A-34B at the completion of smoothing with wrinkles smoothed flat. Although not shown in FIGS. 33A-35, smoothing the shirt additional can include repositioning and smoothing one or both sleeves independent of smoothing the torso portion of the shirt.

Similarly, FIGS. 36A-B depict an example sequence of smoothing pants sequentially on either side of a clamp rod to remove wrinkles and straighten twisted and/or angular protrusions, and FIG. 37 depicts the pants of FIGS. 36A-36B at the completion of smoothing. Although the pants are clamped in the middle of the legs and smoothed on either side of that middle clamp position, in alternative implementations, as previously described, clamping a waist band and independently smoothing each leg with the sweep rod or blade oriented substantially perpendicular to the longitudinal access of each leg can be advantageous for untwisting and unfurling folded over portions. Additionally or alternatively, in implementations, the controller can rotate the platform to align each leg for individual clamping and smoothing.

If the at least one clamp rod 7200, 7200a-b is not centered, the controller 7005 instructs at least one of the sweep rod 7400 and sweep blade 7650 to sweep S1275 under the article, away from the at least one clamp rod 7200, move atop the article 7300, return S1280 to the first starting positioning, and sweep the at least one of the sweep rod 7400 and sweep blade 7650 over the article, away from the at least one clamp rod 7200, 7200a-b.

The method 1200 comprises determining S1290 whether more smoothing is necessary, e.g., wrinkles or folded over portions of the article are still detected by the one or more sensors, and iteratively repeat smoothing beneath and over the article until no additional smoothing is required or a maximum number of attempts (e.g., no more than 3 attempts) are executed. In implementations, the method comprises determining S1265 whether one or more wrinkles or folded over portions of the article would be smoothed best by rotating the article relative to the at least one clamp rod 7200, 7200a-b and the at least one of a sweep rod 7400 and a sweep blade 7650. If additional smoothing is determined to be recruited, the method comprises rotating S1270 the platform 7100 to a desired angle and returning to anchoring S1215 the article with the one or more clamp rods 7200, 7200a-b.

If the at least one clamp rod 7200 is determined S1225 to be centered, the method includes sweeping beneath and over the article on either side of the at least one clamp rod 7200, 7200a-b as described above with regard to FIGS. 31A-B and 32A-B. As shown in FIG. 30, the method includes the controller 7005 instructing at least one of the sweep rod 7400 and sweep blade 7650 to sweep S1230 under the article, away from the at least one clamp rod 7200 in one of an east to west direction or a west to east direction, move atop the article 7300, return S1235 to the first starting positioning, and sweep the at least one of the sweep rod 7400 and sweep blade 7650 over the article, away from the at least one clamp rod 7200, 7200a-b in the same direction as the under article sweep. The method comprises determining S1240 whether more smoothing is necessary, e.g., wrinkles or folded over portions of the article are still detected by the one or more sensors, and iteratively repeat smoothing beneath and over the article until no additional smoothing is required or a maximum number of attempts (e.g., no more than 3 attempts) are executed.

If no additional smoothing is required, the method comprises moving S1245 the at least one of the sweep rod 7400 and sweep blade 7650 over the at least one clamp rod 7200,

45

7200a-b, sliding the at least one of the sweep rod 7400 and sweep blade 7650 between the platform 7100 and the article 7300 and stopping adjacent the at least one clamp rod 7200, 7200a-b at a second starting position. The method 1200 includes the controller 7005 instructing at least one of the sweep rod 7400 and sweep blade 7650 to sweep S1250 under the article, away from the at least one clamp rod 7200 in the other of an east to west direction or a west to east direction opposite the direction of motion on the first side of the clamp 7200, move atop the article 7300, return S1255 to the second starting positioning, and sweep the at least one of the sweep rod 7400 and sweep blade 7650 over the article, away from the at least one clamp rod 7200, 7200a-b in the same direction as the under article sweep. The method comprises determining S1260 whether more smoothing is necessary, e.g., wrinkles or folded over portions of the article are still detected by the one or more sensors, and iteratively repeat smoothing beneath and over the article until no additional smoothing is required or a maximum number of attempts (e.g., no more than 3 attempts) are executed.

In implementations, the method comprises determining S1265 whether one or more wrinkles or folded over portions of the article would be smoothed best by rotating the article relative to the at least one clamp rod 7200, 7200a-b and the at least one of a sweep rod 7400 and a sweep blade 7650. If additional smoothing is determined to be recruited, the method comprise s rotating S1270 the platform 7100 to a desired angle and returning to anchoring S1215 the article with the one or more clamp rods 7200, 7200a-b.

In implementations, sweeping at least one of the sweep rod 7400 and sweep blade 7650 under the article, away from the at least one clamp 7200, 7200a-b comprises raising the deformable article 7300 up above the surface of the platform, and slidably moving until the at least one of the sweep rod 7400 and sweep blade 7650 disengages from the deformable article. In implementations, the at least one of the sweep rod 7400 and sweep blade 7650 can move diagonally upward as it slides along the support rails to assist with unfurling any wrinkled or folded over portions of the article.

Returning now to FIG. 25, after the completion of smoothing or upon determining smoothing is unnecessary, the method 1100 comprises instructing the at least one of the sweep rod 7400 and/or blade 7650 to fold. Folding comprises slidably moving S1130 the elongated sweep rod and/or blade in a first direction toward the at least one clamp 7200, 7200a-b to a position adjacent and parallel to the at least one clamp 7200, 7200a-b, the elongated sweep rod 7400 and/or blade 7650 being disposed between the deformable article and the surface. In implementations comprising the elongated sweep rod, the sweep rod can rotate about a longitudinal axis while slidably moving to assist with sliding beneath the article and subsequently to assist with extracting from the folded portion of the article 7300. In implementations, the at least one movable sweep rod is configured to slide under a terminal edge of the unclamped portion of the article 7300 while rotating. In examples, the elongated sweep rod comprises a circular cross section and rotates about a central axis. In examples, the elongated sweep rod rotates under the deformable article clockwise while sliding from the right of the at least one clamp rod to left and counterclockwise while sliding from the left of the at least one clamp rod to right. Additionally or alternatively, the elongated sweep rod rotates under the deformable article counterclockwise while sliding from the right of the at least one clamp rod to left and clockwise while sliding from

46

the left of the at least one clamp rod to right. In examples, the sweep rod rotates in a range of about 5 to 500 RPM.

With the sweep rod 7400 and/or blade 7650 under the article 7400 and adjacent the at least one clamp rod 7200, 7200a-b, the method comprises raising S1132 the deformable article up and over the at least one clamp rod 7200, 7200a-b while slidably moving in the first direction at least until the article 7300 disengages from the elongated sweep rod and/or blade, retracting S1134 the clamp until disengaged from the article, and determining S1136 whether the article comprises the at least one final fold dimension (e.g., a final footprint area).

In examples, the method further comprises communicating with a packing robot 8000 configured to receive the deformable article from the platform upon stopping iterating the folding sequence.

In examples, the method further comprises instructing a packing robot 8000 in communication with the network to retrieve the deformable article upon stopping iterating the folding sequence.

In examples, the method further comprises instructing a tilt motor of the platform to tilt the platform around a table pivot 7120 to slidably release the deformable article to a receiving platform upon stopping iterating the folding sequence.

Returning now to the step of determining S1112 whether a specific article type fold routine is required, on implementations, the plurality of specific folding routines comprises at least one of a pants folding algorithm, an open front top folding algorithm, a shirt folding algorithm, a hooded sweatshirt folding algorithm, and an algorithm for querying specific customer requests for folding one or more particular articles or article types in a load of household laundry. The specific article type fold routines ensure stable, presentable folds for particular article types. Additionally, the specific article type fold routines assist with folding particular article types to target dimensions for stable, efficient packing with as level a top surface as possible to preventing leaning or toppling within a stack of folded articles.

Taking FIGS. 38-40C together, an implementation for folding a shirt is shown. In implementations, the controller 7005 is configured to determine the article 7300 is a shirt based on processing the one or more received sensor signals 7160, 7160a-c with at least one of a neural network, a regressor, and a size-invariant image database. Additionally or alternatively, a preceding robot in the process line 100, e.g., the repositioning robot 6000, can communicate with the folding robot 7000 via the communication network 230 and provide data indicative of the article being a shirt based on at least one of one or more sensors of the repositioning robot and one or more executed reposition movements indicative of the article being a shirt. Additionally, the repositioning robot can communicate at least one of whether the shirt is an open front shirt, whether the front is facing upward or downward on the surface 7105, and whether the shirt is already partially folded by the repositioning robot. In implementations, the controller 7005 is configured to compare the received output signal to data stored in a memory in communication with the controller for determining the article type. The controller can identify features indicative of at least one of a front side and a back side of the deformable article. In examples, the method can further comprise identifying features indicative of the deformable article being inside out. The identifiable features indicative of the deformable article being inside out comprises at least one a visible seam, a tag, and stitching.

Turning now to FIGS. 38 and 40, an implementation of a method 1300 of determining target folded rectangle dimensions for a shirt is shown. The method 1300 comprises detecting S1302 an article type and determining S1304 the article is a shirt as described previously with regard to implementations. The method 1300 comprises determining S1306 an initial guess of target final rectangle dimensions WT×LT, measuring 51308 flat shirt dimensions WC, WA, and WB, and determining S1310 smallest width WS, where the smallest width WS is equal to the minimum of the measured shirt dimensions WA and WB. The method 1300 comprises selecting targeted folded rectangle dimensions depending on one or more determined conditions. The method 1300 comprises determining S1312 whether a measured length L of the article is less than a guessed target final rectangle length LT plus a is the minimum allowable fold size (MINFOLD) or whether the smallest determined width of WA and WB is less than a guessed target final rectangle width WT minus a tolerance (TOL) for the width/length dimensions. In implementations the minimum allowable fold size (MINFOLD) is defined by the article stiffness and a fold direction (e.g., X-axis Tx) dimension of the at least one clamp 7200. In implementations, the minimum allowable fold size (MINFOLD) accounts for a bend allowance. In implementations, the minimum allowable fold size (MINFOLD) is determined initially for an unfolded garment and increases as the number of layers in a folded garment increase. In implementations, MINFOLD is in a range of between about 2" to 4" (e.g., 5 cm to 10 cm). In implementations, the tolerance (TOL) is predetermined by at least one of packing box dimensions and other packing queuing and loading components of the packing robot 8000. If either condition of the determination S1312 is met, the method comprises selecting S1325 a smaller target rectangle dimensions to which the shirt will be folded for packing. For example, if the initial guess target final rectangle dimensions are 10 inches by 12 inches, if the measured length L is less than 15 inches and the smallest width WS is less than 9 inches, the method comprises selecting S1325 a smaller target rectangle dimensions to which the shirt will be folded for packing.

If neither condition is met at the determining S1312 step, the method 1300 comprises determining S1316 whether WC is greater than the guessed target final rectangle width WT. If that determination is true, the method comprises selecting S1318 reverse target rectangle dimensions LT×WT. For example, if the initial guess target final rectangle dimensions are 10 inches by 12 inches and WC is less than 10 inches, the reverse target folded rectangle dimensions are 12×10.

If the determination S1316 is not true, the method 1300 comprises determining S1320 whether a measured length L of the shirt is greater than or equal to four thirds the initial guess target final rectangle length LT. If the determination is true, the method comprises selecting S1322 the initial guessed target rectangle dimensions WT×LT. For example, if the initial guess target final rectangle dimensions are 10 inches by 12 inches and if the measured length L of the shirt is greater than or equal to 18 inches, the method selects the initial guessed target rectangle dimensions WT×LT, or 10×12 inches.

If the determination S1320 is not true, the method 1300 comprises determining S1324 whether the smallest width WS is greater than or equal to the guessed target final rectangle width WT plus the tolerance (TOL). If the determination is true, the method comprises selecting S1326 reverse target rectangle dimensions LT×WT. For example, if the initial guess target final rectangle dimensions are 10

inches by 12 inches, the tolerance TOL is 1", and WS is greater than or equal to 11", the reverse target folded rectangle dimensions are 12×10 inches.

If the determination S1324 is not true, the method 1300 comprises selecting S1326 smaller target rectangle dimensions. The determination S1324 thus ensures the folded article will fit inside the packing box of known dimensions. As described previously with regard to implementations, final folded dimensions of an article are at or within the bounds of a plurality of predetermined rectangle sizes. Additionally, in implementations, the plurality of predetermined rectangle sizes are dimensioned such that they can be combined to fit alone or in multiple side by side stacking positions to fit within a packing box (e.g., a shipping container 7800, FIG. 27). For example, the rectangle sizes can comprise, in one implementation, a largest rectangle size of medium rectangle size of 10×12 and a smallest rectangle size of at least one of 5×6 and 6×10.

Taking FIGS. 39 and 40 together, an implementation of a method 1400 of folding the shirt to the selected target folded rectangle dimensions comprises clamping S1402 at one edge of the target rectangle width WT, folding S1404 the remainder across the shirt, clamping S1406 at the opposite edge of the target rectangle width WT, and folding S1408 the opposite remained across the shirt. The method 1400 comprises determining S1410 whether the shirt body and sleeves are within the target width WT. If this determination S1410 is not true, the method 1400 returns to the clamping S1402, S14056 at the first edge and second edge of the target rectangle and iterates folding across the shirt in both directions until the shirt body and sleeves are within the target width. The method 1400 then comprises determining S1416 whether a measured length L of the shirt is less than twice the initial target guess length LT. If this determination S1416 is true the method comprises rotating S1418 the platform (e.g., rotating clockwise C or counterclockwise CCW) and clamping S1420 at a position along the shirt that is located at twice the initial guess length (e.g., 2Lt) minus a bend allowance from the top or at least two inches in from the bottom edge plus a bend allowance, whichever location is closer to the top edge (the neck hole edge) of the shirt. The method 1400 then comprises folding the remainder of the shirt up toward the top edge, over the at least one clamp rod 7200. The method then comprises clamping S1424 at LT plus a bend allowance and folding S1426 the shirt top edge down, toward the bottom and over the at least one clamp 7200.

If the determination S1416 is not true, the method comprises rotating S1428 the platform and clamping S1424 at LT plus a bend allowance and folding S1426 the shirt top edge down, toward the bottom and over the at least one clamp 7200.

The bend allowance is defined as, at a minimum, the amount of distance from an edge of the article needed to wrap around the outside edge and top of the clamp rod 7200 during folding (e.g., the clamp rod 7200 is engaged with an outside edge along the fold line). At a minimum, the bend allowance comprises a distance equal to the height of the clamp rod 7200 plus the width of the clamp rod 7200 because the article 7300 will wrap around the clamp rod 7200 when folded. In implementations, the bend allowance is greater than this minimum distance because the fabric of the article has a thickness. A perimeter of an outer diameter of the folded article at the fold bend will increase for thicker article fabrics and/or as the article is folded into more layers. In one example, the bend allowance for all fabric thicknesses comprises a distance of between about 0.25 to 0.75" (e.g.,

approximately 0.5 cm to 2 cm) for a clamp rod **7200** comprising a diameter of 0.25" (e.g., 0.6 cm). In implementations, the bend allowance increases with at least one of thicker fabric and larger clamp rods. In implementations, the controller is configured to dynamically adjust the bend allowance to account for folded thickness by at least one of determining a thickness based on an output signal from the one or more sensors **7160**, **7160a-c** (e.g., a depth camera) and detecting or measuring a height of the clamp rod at a force value indicative of contact with the article as measured by a force sensor disposed on the clamp rod and/or Z-axis motor **7405**, **7405a-b**.

Taking FIGS. **41-45E** together, an implementation for folding pants is shown. In implementations, the controller **7005** is configured to determine the article **7300** is pants based on processing the one or more received sensor signals **7160**, **7160a-c** with at least one of a neural network, a regressor, and a size-invariant image database. Additionally or alternatively, a preceding robot in the process line **100**, e.g., the repositioning robot **6000**, can communicate with the folding robot **7000** via the communication network **230** and provide data indicative of the article being pants based on at least one of one or more sensors of the repositioning robot and one or more executed reposition movements indicative of the article being pants. Additionally, the repositioning robot can communicate at least one of whether the front side of the pants is facing upward or downward on the surface **7105**, and whether the pants are already partially folded by the repositioning robot. In implementations, the controller **7005** is configured to compare the received output signal to data stored in a memory in communication with the controller for determining the article type. The controller can identify features indicative of at least one of a front side and a back side of the deformable article. In examples, the method can further comprise identifying features indicative of the deformable article being inside out. The identifiable features indicative of the deformable article being inside out comprises at least one a visible seam, a tag, and stitching.

Turning now to FIGS. **41-42** and **45A-E**, an implementation of a method **1200** of determining target folded rectangle dimensions for pants is shown. An implementation of a method **1500** of determining target folded rectangle dimensions for pants comprises detecting **S1502** an article type and determining **51504** that the article is pants as described previously with regard to implementations. The method **1500** comprises determining **S1506** an initial guess of target final rectangle dimensions $WT \times LT$, measuring **S1508** flat pants width dimensions $W0$, WA , and WB at various locations along the length of the pants and measuring a length L . The method **1500** comprises selecting targeted folded rectangle dimensions depending on one or more determined conditions. The method **1500** comprises determining **51510** whether a measured length L of the article is greater than twice the initial guess target length LT . If the determination **S1510** is not true, the method **1500** comprises executing **51512** a non-specific article type folding routing (e.g., a general folding routine **S1116**).

If the determination **51510** is true, the method comprises determining **51514** whether the measured width dimension $W0$ at the pants waistband is less than a first threshold value $T2A$, where the initial guess width WT is less than $T2A$ and $T2A$ is less than one and half times the initial guess width WT . If that determination is true, the method comprises selecting **S1516** smaller target rectangle dimensions. For example, if the initial guess rectangle dimensions are 10×12

inches and the measured waistband width $W0$ is less than 13 inches the method **1500** selects smaller target rectangle dimensions.

If the determination **51514** is not true, the method **1500** comprises determining **S1518** whether a measured width WB is greater than or equal to twice the initial guess width WT minus the tolerance (TOL) and less than twice the initial guess width WT plus the tolerance. If the determination is true, the method **1500** comprises executing **S1520** a half fold to the initial guessed target rectangle dimensions $WT \times LT$. For example, if the initial guess rectangle dimensions are 10×12 , the tolerance is 1", and the measured width WB is greater than or equal to 19 inches and less than or equal to 21 inches, the method **1500** executes **51520** a half fold to the initial guessed target rectangle dimensions $WT \times LT$, or 10×12 inches.

If the determination **S1518** is not true, the method **1500** comprises determining **S1522** whether a measured width WA is greater than or equal to twice the initial guess length LT minus the tolerance (TOL) and less than twice the initial guess length LT plus the tolerance (TOL). If the determination is true, the method **1500** comprises executing **S1524** a half fold to the reverse initial guessed target rectangle dimensions $LT \times WT$. For example, if the initial guess rectangle dimensions are 10×12 and the measured width WA is greater than or equal to 23 inches and less than or equal to 25 inches, the method **1500** executes a half fold to the reverse initial guessed target rectangle dimensions $LT \times WT$, or 12×10 inches.

If the determination **51522** is not true, the method **1500** comprises determining **S1526** whether a measured waistband width $W0$ is greater than the initial guess width WT plus two times the minimum allowable fold size ($MIN-FOLD$) and less than or equal to a second threshold $T2B$ value. In implementations, $T2B$ is a value in a range of between about the target length plus twice the minimum allowable fold size ($LT + 2MINFOLD$) to three times the target width plus twice the bend allowance ($3WT + 2BA$) for producing a stable and aesthetically pleasing fold. If the determination is true, the method **1500** comprises executing **S1528** a thirds fold to the initial guessed target rectangle dimensions $WT \times LT$. For example, if the initial guess rectangle dimensions are 10×12 and the measured waistband width $W0$ is greater than or equal to 16 inches and less than or equal to 31 inches, the method **1500** executes a thirds fold to the initial guessed target rectangle dimensions $WT \times LT$, or 10×12 inches.

If the determination **51526** is not true, the method **1500** comprises determining **S1530** whether a measured waistband width $W0$ is greater than the second threshold $T2B$ value and less than three times the initial guess length LT plus twice the bend allowance BA . If the determination **S1530** is true, the method **1500** comprises executing **S1531** a thirds fold to reverse initial guessed target rectangle dimensions $LT \times WT$. For example, if the initial guess rectangle dimensions are 10×12 and the measured waistband width $W0$ is greater 28 inches and less than 37 inches, the method **1500** executes a thirds fold to the reverse initial guessed target rectangle $LT \times WT$, or 12×10 inches.

If the determination **51530** is not true, the method **1500** comprises determining **S1534** whether a measured width WA is greater than or equal to three times the initial guess length LT . If the determination **51534** is true, the method **1500** comprises folded the pants to a full box target rectangle dimension $BW \times BL$. If the determination **51534** is not true, the method comprises executing **S1538** a default half fold method **1600**. In implementations, the default half fold

51

method comprises determining **S1605** whether the absolute value of the difference between measured width **WB** and twice the initial guess width **WT** is less than the absolute value of the difference between the measured width **WA** minus twice the initial guess length **LT**. If the determination is true, the method **1600** comprises executing **51615** a half fold to the guessed target rectangle dimensions **WT**×**LT**. If the determination **S1605** is not true, the method **1600** comprises executing **S1610** a half fold to reversed guessed target rectangle dimensions **LT**×**WT**. For example, for initial guess dimensions of 10×12 inches if measured width **WB** minus 20 is less than measured with **WA** minus 24, the method **1600** is configured to execute a half fold to the guessed target rectangle dimensions, 10×12 inches. Otherwise, the method **1600** is configured to execute a half fold to reverse guessed target rectangle dimensions, 12×10 inches.

As described previously with regard to implementations, final folded dimensions of an article are at or within the bounds of a plurality of predetermined rectangle sizes. Additionally, in implementations, the plurality of predetermined rectangle sizes are dimensioned such that they can be combined to fit alone or in multiple side by side stacking positions to fit within a shipping container for example, the rectangle sizes can comprise, in one implementation, a largest rectangle size of 10×24, medium rectangle size of 10×12 and a smallest rectangle size of at least one of 5×6 and 6×10. In implementations, as shown in FIG. 45A, measured width **W0** is the width of the pants at the waistband **W0**, measured width **WA** is the measured width from outer edge to outer edge of the unfolded pants at a point lower down from the waistband **W0** and above measured width **WB**. In implementations, for example **WA** can be measured at 20 inches down from the waistband and **WB** can be measured at 24 inches down from the waistband **W0**.

Taking FIGS. 43-45 together, folding the pants to the target folded rectangle dimensions comprises include executing a “half fold” method **1700** or a “thirds fold” method **1800** depending on the measured dimensions of the pants as detected by the one or more sensors **7160a-c** and determined by the controller **7005**.

In implementations, the half fold method **1700**, as depicted in FIGS. 43 and 45A-C comprises folding **S1705** a bottom of each leg up so that overall measured length of the folded pants is **2LT** and the ankle ends **AE1**, **AE2** are above **LT** by distance **delta A**. In implementations, each leg can be folded independently with the platform rotated such that the clamp rod is perpendicular to a longitudinal axis of each leg for precise alignment of the folded over lower leg portion atop the upper leg portion. Alternatively, in implementations, the legs can be folded simultaneously. The distance **delta A** is the amount of fabric clamped. In implementations, the distance **delta A** is in a range of between about 1 cm to 4 cm. Clamping the ankle ends **AE1**, **AE2** prevents the folded pants legs from unfolding, especially during subsequent maneuvers and thereby maintains a precise, compact fold. The method **1700** comprises clamping **S1710** the pants at **LT** minus a bend allowance. The method **1700** comprises folding **S1715** a bottom half up (e.g., both legs together, simultaneously folded up in one sweep) over the at least one clamp **7200** so the overall length of the partially folded pants is **LT**. The method **1700** comprises rotating the platform **7100** (e.g., rotating clockwise **C** or counterclockwise **CCW**) and clamping **51720** the pants vertically at a midpoint of the waistband **WC** and folding **S1725** the pants in half lengthwise over the at least one clamp so that the folded width is less than or equal to **WT**.

52

In implementations, the thirds fold method **1800**, as depicted in FIGS. 44 and 45D-E comprises folding **S1805** the bottom of each leg up so that the measured length is **2LT**. The method comprises locating **S1810** a center of the waistband **WC** and centering **S1815** a target width **WT** on **WC**. The method **1800** comprises clamping **S1820** vertically just inside (e.g., accounting for **BA**) a left edge of the target rectangle (**WC**−**WT/2**+**BA**) and folding **S1825** the left third lengthwise over the at least one clamp rod **7200**. The method **1800** comprises clamping **S1830** vertically just inside (e.g., accounting for **BA**) a right edge of target rectangle (**WC**+**WT/2**−**BA**), and folding **51835** a right third of the pants lengthwise over the at least one clamp **7200**. The method comprises rotating **S1840** the platform 90 degrees (e.g., rotating clockwise **C** or counterclockwise **CCW**) and clamping at **LT** plus a bend allowance. The method comprises folding a top half of the pants down over the at least one clamp so the measured length of the folded pants is **LT**.

The bend allowance is defined as, at a minimum, the amount of distance from an edge of the article needed to wrap around the outside edge and top of the clamp rod **7200** during folding (e.g., the clamp rod **7200** is engaged with an outside edge along the fold line). At a minimum, the bend allowance comprises a distance equal to the height of the clamp rod **7200** plus the width of the clamp rod **7200** because the article **7300** will wrap around the clamp rod **7200** when folded. In implementations, the bend allowance is greater than this minimum distance because the fabric of the article has a thickness. A perimeter of an outer diameter of the folded article at the fold bend will increase for thicker article fabrics and/or as the article is folded into more layers. In one example, the bend allowance for all fabric thicknesses comprises a distance of between about 0.25 to 0.75" (e.g., approximately 0.5 cm to 2 cm) for a clamp rod **7200** comprising a diameter of 0.25" (e.g., 0.6 cm). In implementations, the bend allowance increases with at least one of thicker fabric and larger clamp rods. In implementations, the controller is configured to dynamically adjust the bend allowance to account for folded thickness by at least one of determining a thickness based on an output signal from the one or more sensors **7160**, **7160a-c** (e.g., a depth camera) and detecting or measuring a height of the clamp rod at a force value indicative of contact with the article as measured by a force sensor disposed on the clamp rod and/or **Z**-axis motor **7405**, **7405a-b**.

Taking FIGS. 50-54 together, in implementations, a specific article type folding routine can comprise executing a customer request **S1114c** for a particular folding sequence. In implementations, the customer request routine **S1114c** comprises receiving one or more folding instructions from a remote device **7900** in operable communication with the network. As shown in FIGS. 50 and 52-54, the one or more folding instructions comprises user inputs to at least one of a computer portal and smartphone display running an application operating on a display screen **7905** for receipt of one or more user inputs, such as touch screen taps. As shown in FIG. 50, the user device comprises a display screen **7905** comprising at least one of graphics **7910**, one or more text fields **7912**, **7914** for conveying information, and interactive fields **7916**, such as selectable radio buttons, selectable text boxes, or drop-down menus that eliciting interactive input from the customer (e.g., device user) and, once pressed or tapped, communicate actionable information to the controller via a wired or wireless communication network. For example, in FIG. 50, a display screen **7905** shows the customer a picture of twisted pair of pants prior to execution of a general folding routine rather than a pants type folding

routine, the image being taken by the one or more sensors **7160a-c** disposed adjacent a folding device **7000** platform **7100** on which the twisted pants were delivered for folding. The display screen can also include text indicia **7912** explaining the article type was not recognized by the autonomous folding device **7000** and that a general fold was performed to fit the article within a preferred finish folding rectangle size. Additionally, in implementations, the display screen provides text indicia **7914** querying the customer about an interest in continuing to receive such alerts and radio buttons **7916** for receiving and transmitting a user response to the controller **7005** of the folding device **7000**. Additionally, a graphic display screen may appear to the user indicating the relative size and placement of the target rectangle **7812** defining the outer bounds of the folded deformable article.

Additionally, the application running on the remote device **7900** can display to the user a query **7914** for customer identification of the article type. For example, the query **7914** of FIG. **52** asks the customer whether the customer recognizes the article type of the article displayed on the screen **7905**. Interactive fields, such as selectable radio buttons, selectable text boxes, or a drop-down options menu **7918a** eliciting interactive input from the customer (e.g., device user) and, once pressed or tapped, communicate actionable information to the controller via a wired or wireless communication network. Here, the customer can indicate via pull down menu options whether or not the deformable article is a recognized type. If the customer indicates recognition of the article, in implementations, such as the display of FIG. **53**, the remote device **7900** queries the customer to specifically identify the article type. For example, the customer can select from a plurality of categories provided in a drop-down menu **7918b**. The folding device **7000** can store this image tagged with a customer-identified article type in a database or other memory store and increase the likelihood over time of learning to identify article types for insufficiently repositioned articles and using that identification to select a most appropriate folding routine.

Additionally or alternatively, implementations, the one or more user inputs to the display screen **7905** comprises at least one of a preferred at least one final dimension, such as a final width and/or length of a target rectangle **7812** for the folded deformable article, a user defined folded rectangle bounding box, a request for not folding the deformable article, and a submission of one or more specified fold lines and an order of folding. As shown in FIG. **54**, a preferred sequence for folding the deformable article at each of the one of the one or more specified fold lines is indicated by a user tracing fold lines across a displayed image of an article disposed on the platform of a folding robot for folding. The application can ask with text **7920** whether the customer would like to invert folds, for example if a shirt is upside down on the platform **7100**. Another text field **7922** can prompt the customer to draw preferred fold lines in a preferred order of folding. A controller **7005** receiving these instructions can then rotation the platform and anchor the article along those indicated fold lines in the order in which they are indicated for sequenced folding.

Although a representative few specific article type folding routines are described herein, other particular folding routines are contemplated for garments such as hooded sweat-shirts having several protruding extremities from a central core and open front shirts received partially folded from the repositioning robot **6000**. Such shirts may be folded inward along a longitudinal bisector of the torso with sleeves

matched together. The sleeve that may require straightening by the sweep rods before being folded onto the torso portion along one or more fold lines. The shirt can then be rotated on the platform and folding again down the length of torso portion along one or more sequential fold lines to end at a final folded area. Although, the list of specific article type fold routines presented herein is non-exhaustive, a plurality of general folding routines are configured to enable the folding robot **7000** to neatly fold any article comprising any type, size, and thickness to a presentable, stable fold that will not unfold or topple during the packing process for return to a customer. The general folding routines can be selected in the order presented vertically in FIG. **25** to more particularly address variation in article size and thickness before defaulting to a most basic recursive folding technique (e.g., recursive fold in half) that results in stacked layers that can be less level and less aesthetically appealing to a customer.

Returning now to the folding method **1100**, in implementations, the method comprises determining **S1112** that general folding routine is required. In implementations, selecting from a plurality of general folding routines **S1116** comprises selecting at least one of a routine for folding in one or more protrusions **S1126a**, a routine for folding a footprint area of a repositioned article to a target size **S1116b**, and a routine for recursively folding an article in half **S1116c**.

For example, taking FIGS. **46-47B** together, in implementations, a method **1900** for folding in a protrusion (e.g., one or more sleeves, pant legs, and hoods), comprises finding a rectangular core of an article (e.g., where human core is—on human torso—belly button of shirt, waistband area of pants), finding the center of the core rectangle, determining what is a protrusion emitted out from core (e.g. sleeve), determining the vectors that describe protrusions into core, planning a generalized fold of the protrusions in toward the center, and folding until the article fits within one or more predetermined box dimensions. As described previously with regard to implementations, final folded dimensions of an article are at or within the bounds of a plurality of predetermined rectangle sizes. Additionally, in implementations, the plurality of predetermined rectangle sizes are dimensioned such that they can be combined to fit alone or in multiple side by side stacking positions to fit within a shipping container for example, the rectangle sizes can comprise, in one implementation, a largest rectangle size of 10×24, medium rectangle size of 10×12, and a smallest rectangle size of at least one of 5×6 and 6×10.

Returning to FIGS. **46-47B**, the method comprises approximating **S1905** a polygon about the detected article **7300**, finding **S1910** a core rectangle RC (FIGS. **47A-B**) within the article, determining **S1915** a center of the core rectangle, identifying **S1920** one or more protrusion(s) extending out from the core rectangle, identifying **S1925** one or more vectors V (FIG. **47A**) into the core rectangle RC, selecting **S1930** a vector from the one or more vectors, determining whether to rotate **S1935** the platform **7100** such that the selected one of the one or more vectors is perpendicular to the at least one clamp rod **7200**, rotating **S1945** the platform if not, clamping **S1940** the at least one clamp rod **7200** perpendicular to the vector, and folding **S1950** the protrusion toward the center in the direction of the vector.

FIG. **47A** depicts a schematic example of a controller generated mask and identification of a core rectangle RC and vectors V defining the fold directions of protrusions into the core rectangle RC in accordance with the method of FIG. **46**. FIG. **47B** depicts a schematic example of a controller generated mask and a plot of distances from an outer

55

perimeter to the core rectangle for identifying protrusions P and executing the method of FIG. 46.

The method 1900 comprises determining 51955 whether the folded protrusion is entirely within the core rectangle. If not, the method iteratively repeats clamping S1940 perpendicular to the vector and folding toward the core rectangle under the protrusion is entirely within the core rectangle. The method then comprises determining S1960 whether there are any remaining vectors defining one or more protrusions needing to be folded into the core rectangle, and if so, the method 1900 returns to the step of selecting S1930 a vector and folding toward the core rectangle. Once no vectors remain outside of the core rectangle, the method comprises determining whether the core rectangle is less than or equal to final target folded rectangle dimensions. If so, the article is folded and ready for packing and if not, the method 1900 returns to a step of selecting a generalized folding routine. In implementations, the method 1900 executes at least one of the fold to a target area routine S1116a and the recursively fold in half routine S1116c to reduce the core rectangle to at or within target dimensions.

Turning now to FIGS. 48A-B, a routine for folding a repositioned article 7300d to a target size S1116b comprises determining one or more fold lines 7320a'-e' and a sequence of folding an article over one or more clamp rods placed sequentially at the determined fold lines to produce a folded article 7300d having final dimensions equal to or within a target fold area WT×LT. For example, in FIG. 48A, the article 7300d is configured to be folded in thirds, sequentially, at fold lines 7320a'-c', and then the controller will rotate the platform 7100 and fold in a direction perpendicular to fold lines 7320a'-c' along fold lines 7320d' and 7320e' to end up in an upper right quadrant at or within final folded dimensions of width WT by length LT. This general folding method is applicable to all article types, sizes, and thicknesses presented in any random order for folding. For example, FIGS. 22A-B depict two disparate article types folded sequentially along predetermined fold lines 7320a-f and 7320g-h to fold each article 7300a, 7300b to a final target area.

Deciding where to place the one or more fold lines 7320 includes any of the previously described considerations and at least one of determining a final fold area and considering an article thickness t, as shown in FIG. 48B. Because the article 7300d will fold over the one or more clamp rods, which have a height RH, the overall stack height before clamp retraction will be 2t plus RH and will require a sufficient folded over top portion to prevent the article from springing back and unfolding. In implementations of this folding routine of folding to a target area S1116b and in implementations of all general and specific folding methods, to account for the overall stack height and prevent flap back of the folded over portion of an article, the controller 7005 clamps at a minimum distance from an edge of an article in a range of between about 1 to 5 inches (e.g., 2.54 cm to 12.7 cm) for a clamp having a height RH and width each in a range of between about 0.25 inch to 1.5 inches (e.g., 0.6 cm to 3.81 cm).

Turning now to FIGS. 49A-D, a routine for folding a repositioned article 7300e to a target rectangle size comprises recursively folding the longest dimension in half until the article 7300e is at or within the target rectangle size. For example, as shown in FIG. 49A, the longest edge is folded over fold line 7320a" to go from 2LT to a target length of LT, resulting in the dimensions and orientation depicted in FIG. 49B. The controller 7005 is configured to rotate the platform 7100 in the direction of either of the clockwise arrow C or

56

the counter clockwise arrow CCW so that the at least one clamp 7200 is aligned with a second fold line 7320b" aligned perpendicular to a longest length. The controller 7005 then instructs the at least one clamp rod 7200 to clamp the article 7300e and at least one of the sweep rod 7400 and sweep blade 7650 to fold the article over fold line 7320b". The width of the article 7300e reduces from 2WT in FIG. 49C to WT in FIG. 49D, thereby resulting in final folded rectangle dimensions WT×LT. In implementations, depending on starting dimensions, an article may be folded over in the same direction two or more times before the longest dimension is parallel to the at least one clamp rod 7200. In implementations, the controller 7005 is configured to fold perpendicular to the longest dimension to produce a stable fold, as wide and flat as possible.

In any of the general folding method implementations, deciding where to clamp can be determined based on at least one of article size and material thickness. For example, in implementations, the controller can determine, based on a mask (e.g., FIG. 26) where the article is on the platform 7100 and move the at least one clamp 7200 until the clamp is over the area that is mostly white (e.g., 85% white) and not black, thereby indicating the presence of the article 7300. In implementations, the controller 7005 can then instruct the clamp to move in 50 mm and clamp the article for smoothing. In implementations, the controller can instruct the at least one clamp 7200 to move in at least 2 inches and clamp for folding. In implementations, the controller can instruct the at least one clamp 7200 to move in from the terminal edge of the article by a distance in a range of between about 2 to 6 inches (e.g., 50 mm to 150 mm) before lowering to a clamped position atop the article 7300. In implementations, the controller is configured to dynamically determine a clamping positioned based on at least one of the accrued number of folds and a difference in a maximum height and a minimum height of a top surface of the article from the surface 7105 of the platform 7500. The maximum and minimum height can be measured by the one or more sensors 7160, 7160a-b and the controller can compare the difference to a threshold indicative of a maximum allowable slope, or lean, of the top of the folded article. For example, the threshold can be in a range of between about 1 to 3 inches (e.g., 25 mm to 75 mm) such that the folded article can be stacked with other folded articles in a stable stack in a packing queue and/or packing container without toppling. Additionally or alternatively, the controller is configured to detect a slope of the top surface based on the output signal of the one or more sensors 7160, 7160a-b and compare an angle of the slope relative to the horizontal plane of the platform surface 7105 to a threshold angle. For example, the threshold angle indicative of an acceptable top surface slope can be in a range of between about 0 to 30 degrees. In implementations a threshold maximum allowable tilt angle for the top surface that ensures stable stacking of two or more articles is around about 15 to 20 degrees. Additionally or alternatively, the controller can decide where to clamp an article based on an aspect ratio, for example, clamping perpendicular to a longitudinal length and folding over the at least one clamp in the direction of the longest dimension. Additionally or alternatively, the controller can instruct the clamp to clamp along a fold line that is not a bisector of the article but is offset such that the article is folded by an amount that less than being folded in half. This can be particularly advantageous in a final folding pass for achieving a target width or length for fitting within target packing dimensions and producing a stable fold that does not unfurl during packing and shipping.

57

As described herein with regard to implementations, the folding device **7000** is configured to fold a plurality of article types, sizes, and thicknesses presented in any order. The folding device **7000** is configured to accommodate variations common in loads of household laundry and fold each article of the plurality of types, sizes, and thicknesses to target uniformity for stable and aesthetically pleasing final folded states. The platform of the folding device rotates so that the plurality of article types and sizes can be received in any orientation and rotated precisely for alignment of a best suited fold line with a clamp rod. In implementations, the fold lines can be determined dynamically for each unique article and with each iteration of folding without requiring any human intervention to modify settings or swap out mechanical components. Additionally, because the articles are fully folded within the perimeter of the rotatable platform, the active folding area is consolidated to a single area rather than spread out down a line of sequentially moving components or sequential devices for performing various folds in various fold directions.

As described previously with regard to implementations, a deformable article **7300** is delivered to the folding device **7000** by a repositioning robot **6000**. In implementations, the repositioning robot **6000** directly deposits the deformable article onto the rotatable platform **7100** of the folding device. In other implementations, as shown in FIGS. **55-58**, a transfer conveyor **6070** transits between the repositioning robot **6000** and the folding device **7000** to transfer repositioned articles **7300** onto the rotatable platform **7100** for folding.

Referring to FIG. **58**, a leading edge **6031** of a conveyor **6030** of a repositioning robot **6000** is shown in conjunction with a transfer conveyor **6070** configured to be disposed outside a work volume of the repositioning robot **6000**. In implementations, a conveyor **6030** disposed at the bottom of the work volume can have an angled leading edge **6031** configured to nest with an angled receiving end **6071** of the transfer conveyor **6070**. The nested ends preventing transferred repositioned laundry articles from crumpling or getting stuck between the two overlapped moving conveyors **6030**, **6070**. The matching angles of the leading edge **6031** and the receiving end **6071** and the matching driving directions (e.g., run direction R) ensures that no part of a transferring article falls between the floor conveyor **6030** and the transfer conveyor **6070**. Additionally, a flatter angle of the receiving end **6071** of the transfer conveyor **6070** prevents the transferring article from crumpling during transfer. In implementations, a gap G between the conveyor **6030** and the transfer conveyor **6070** is no greater than 10 mm. In implementations, the gap G is between about 5 mm to 10 mm.

As shown in FIGS. **55A-B**, in implementations, the transfer conveyor **6070** is configured to move back and forth on one or more rails **6072a-b**, **6072'** between the repositioning robot **6000** and the folding robot **7000**. The transfer conveyor **6070** is configured to deposit the repositioned deformable laundry article **7300** received by the transfer conveyor **6030** onto a receiving surface of the folding robot **7000**. In implementations, the depositing end **6072** of the transfer conveyor **6070** comprises an angled downward slope for delivering the repositioned article **7300** onto the rotatable platform **7100**. The depositing end **6072** slides over the surface **7105** of the platform **7100** and comprises a clearance in a range of between about 0.25 mm to 5 mm. In implementations, as shown in FIG. **55A**, a pair of rails **6072a-b** extend beyond a center axis (diameter) of the platform **7100** and on either side of the platform so the depositing end **6072**

58

of the conveyor **6070** can extend past the middle of the platform **7100** and ensure that larger items are fully deposited on the platform and not hanging off an edge. Additionally or alternatively, in implementations, such as that of FIG. **55B**, the conveyor **6070** is configured to slidably extend out over the platform **7100** upon reaching the end of a guide rail **6072'** aligned with a center of the platform **7100** such that the conveyor **6070** is cantilevered on its motorized, transiting base.

In implementations, the drive motor of the transfer conveyor **6070** is in operable communication with one or both of the repositioning robot controller **6005** and the folding device **7000** controller **7005**. Additionally or alternatively, upon delivering a repositioned article to the folding device **7000**, the transfer conveyor **6070** can retract as it deposits the article onto the platform **7100** of the folding device **7000**. In implementations, once the transfer conveyor **6070** is extended out over the platform **7100**, the controller **7005** is configured to instruct the transfer conveyor **6070** to retract slightly faster than a belt of the conveyor rotates to place the article **7300** on the platform **7100**. The transfer conveyor **6070** thus can persistently drag away from the article **7300** during placement and therefore provide a little stretching and or smoothing of the repositioned article. Additionally or alternatively, the controller **7005** is configured to instruct the one or more clamp rods **7200**, **7200a-b** to clamp the first few inches of the article **7300** as they are disposed on the platform **7100** such that the article **7300** is not dragged across the platform **7100** but is instead stretched and smoothed as the transfer conveyor **6070** retracts slightly faster than the article **7300** is deposited.

In other implementations, the controller **6005** can be configured to instruct one lifter **6105a** and another lifter **6105d** of two or more lifters of the repositioning robot **6000** having associated engaged grippers **6105a,d** to sweep the repositioned one of the plurality of deformable laundry articles **7300** onto a surface outside the work volume. The surface can be, for example, the transfer conveyor **6070** or a surface of the folding robot **7000**. In other implementations, the conveyor **6030** can be replaced by a tilting surface configured to receive thereon a repositioned deformable laundry article and tilt to release the article **7300** under the force of gravity onto another surface such as the transfer conveyor **6070** or a surface of the folding robot **7000**. In other implementations, the conveyor **6030** can be positioned higher than a stationary transfer conveyor partially stacked therebeneath in a waterfall configuration.

Once the deformable article **7300** is folded on the platform **7100**, a retrieving conveyor **8100** operates to extract the folded article **7300**. Turning now to FIGS. **59-61**, the retrieving conveyor **8100** operates similarly to the transfer conveyor **6070**. The retrieving conveyor **8100** is in operable communication with a controller **6005**, **7005** configured to actuate a drive motor to transit the retrieving conveyor **8100** along one or more fixed rails **8105a-b** for aligning the retrieving conveyor **8100** with the folding platform **7100**. In implementations, a belt of the retrieving conveyor **8100** runs at the same speed and in the opposite direction of movement of the retrieving conveyor **8100** as it extends over the platform **7100**. This prevents any need to sense an edge of the folded article **7300**. Additionally or alternatively, in implementations, the controller **7005** receives a signal from one or more sensors **7160**, **7160a-c** configured to detect a proximity of a leading edge **8101** of the retrieving conveyor **8100** to the folded article **7300**. In implementations, a controller **7005** of the folding device **7000** can rotate the platform to orient the folded article to a position within

59

bounds of the fixed landing path of the retrieving conveyor **8100** over the platform **7100**.

Once the leading edge **8101** contacts the folded article **7300**, the rotating conveyor draws the folded article **7300** up in the direction of arrow R1 in FIG. **50**. As described previously with regard to implementations of the folding robot **7000** comprising a blade assembly **7600**, the planar blade **7650** is configured to securely lift a folded article during a movement onto another surface or transport conveyor, such as the retrieving conveyor **8100**. For example, in one implementation, the planar blade **7650** is configured to slide beneath an edge of a folded garment and rotate to lift the edge off of the surface **7105** of the platform **7100** so that the retrieving conveyor **8100** can approach the article and easily slide beneath the lifted edge for receiving the article up onto the conveyor without bumping it and potentially unfolding or toppling the article during extraction from the platform **7100**.

In all of the preceding implementations of the folding device **7000**, the controller **7005** of the folding device is configured to communicate at least one of predicted or achieved footprint area and folded article height with the at least one controller **8005** of the packing and queuing system **8000**.

Additionally or alternatively, in implementations, as described previously with regard to the method **1100** of folding, the controller **7005** of the folding device can determine **S1106** based on one or more received signals that a laundry article is too small for folding. For example, the article could be a baby sock, a pair of underwear, or a long, thin article like a scarf. In such instances, the controller **7005** can instruct the folding device **7000** to forgo folding the laundry article **7300** and instead pass the unfolded laundry article through the remainder of the process line unfolded. A packing robot conveyor or queue platform can receive the article and deposit the unfolded laundry article into one or more containers such that the unfolded articles are deposited in a container prior to loading the one or more folded laundry articles and/or stacks of folded laundry articles from a queue platform into the conveyor. Additionally or alternatively, the packing robot conveyor can deposit the unfolded laundry articles in one or more piles on the queue platform for conveyance in aggregate into a container.

In embodiments, any of the one or more robots in the process line preceding the queueing and packing robot **8000** can determine one or more articles of household laundry is too small for folding and provide the one or more too small for folding laundry articles to the packing station for loading into an empty container. For example, a repositioning robot **6000** can identify and collect in a container the one or more too small for folding laundry articles and the collection container can transit on rails to the packing station, skipping any processing by subsequent robots in the process line and eliminating the time of those subsequent robots having to handle the article.

In embodiments, one or more retrieval arms each including at least one of a power lifter, jib, or crane mounted above or aside at least one of the separation robot **5000**, the repositing robot **6000**, the folding device **7000**, and the packing robot **8000** can retrieve an article determined by one or more sensors and controllers to be too small for folding, carry it to a container at the packing station of the packing robot **8000**, and release the unfolded article into the container. Alternatively, the one or more retrieval arms can comprise a robotic arm on a mobile base for retrieving a too small article from one robot in the process line and transiting

60

across the floor to the packing station for depositing the unfolded laundry article in a container.

All of the methods and tasks described herein may be performed and fully automated by a computer system. The computer system may, in some cases, include multiple distinct computers or computing devices (e.g., physical servers, workstations, storage arrays, etc.) that communicate and interoperate over a network to perform the described functions. Each such computing device typically includes a processor (or multiple processors or circuitry or collection of circuits, e.g., a module) that executes program instructions or modules stored in a memory or other non-transitory computer-readable storage medium. The various functions disclosed herein may be embodied in such program instructions, although some or all of the disclosed functions may alternatively be implemented in application-specific circuitry (e.g., ASICs or FPGAs) of the computer system. Where the computer system includes multiple computing devices, these devices may, but need not, be co-located. The results of the disclosed methods and tasks may be persistently stored by transforming physical storage devices, such as solid-state memory chips and/or magnetic disks, into a different state.

Although the subject matter contained herein has been described in detail for the purpose of illustration, it is to be understood that such detail is solely for that purpose and that the present disclosure is not limited to the disclosed embodiments, but, on the contrary, is intended to cover modifications and equivalent arrangements that are within the spirit and scope of the appended claims. For example, it is to be understood that the present disclosure contemplates that, to the extent possible, one or more features of any embodiment can be combined with one or more features of any other embodiment.

Other examples are within the scope and spirit of the description and claims. Additionally, certain functions described above can be implemented using software, hardware, firmware, hardwiring, or combinations of any of these. Features implementing functions can also be physically located at various positions, including being distributed such that portions of functions are implemented at different physical locations.

Example embodiments of the present inventive concepts may be embodied in various devices, apparatuses, and/or methods. For example, example embodiments of the present inventive concepts may be embodied in hardware and/or in software (including firmware, resident software, microcode, etc.). Furthermore, example embodiments of the present inventive concepts may take the form of a computer program product comprising a non-transitory computer-usable or computer-readable storage medium having computer-usable or computer-readable program code embodied in the medium for use by or in connection with an instruction execution system. In the context of this document, a computer-usable or computer-readable medium may be any medium that can contain, store, communicate, or transport the program for use by or in connection with the instruction execution system, apparatus, or device.

The computer-usable or computer-readable medium may be, for example but not limited to, an electronic, magnetic, optical, electromagnetic, infrared, or semiconductor system, apparatus, or device. More specific examples (a non-exhaustive list) of the computer-readable medium would include the following: an electrical connection having one or more wires, a portable computer diskette, a random access memory (RAM), a read-only memory (ROM), an erasable programmable read-only memory (EPROM or Flash

61

memory), an optical fiber, and a portable compact disc read-only memory (CD-ROM). Note that the computer-usable or computer-readable medium could even be paper or another suitable medium upon which the program is printed, as the program can be electronically captured, via, for instance, optical scanning of the paper or other medium, then compiled, interpreted, or otherwise processed in a suitable manner, if necessary, and then stored in a computer memory.

Example embodiments of the present inventive concepts are described herein with reference to flowchart and/or block diagram illustrations. It will be understood that each block of the flowchart and/or block diagram illustrations, and combinations of blocks in the flowchart and/or block diagram illustrations, may be implemented by computer program instructions and/or hardware operations. These computer program instructions may be provided to a processor of a general purpose computer, a special purpose computer, or other programmable data processing apparatus to produce a machine, such that the instructions, which execute via the processor of the computer or other programmable data processing apparatus, create means and/or circuits for implementing the functions specified in the flowchart and/or block diagram block or blocks.

These computer program instructions may also be stored in a computer usable or computer-readable memory that may direct a computer or other programmable data processing apparatus to function in a particular manner, such that the instructions stored in the computer usable or computer-readable memory produce an article of manufacture including instructions that implement the functions specified in the flowchart and/or block diagram block or blocks.

The computer program instructions may also be loaded onto a computer or other programmable data processing apparatus to cause a series of operational steps to be performed on the computer or other programmable apparatus to produce a computer implemented process such that the instructions that execute on the computer or other programmable apparatus provide steps for implementing the functions specified in the flowchart and/or block diagram block or blocks.

All of the methods and tasks described herein may be performed and fully automated by a computer system. The computer system may, in some cases, include multiple distinct computers or computing devices (e.g., physical servers, workstations, storage arrays, etc.) that communicate and interoperate over a network to perform the described functions. Each such computing device typically includes a processor (or multiple processors or circuitry or collection of circuits, e.g. a module) that executes program instructions or modules stored in a memory or other non-transitory computer-readable storage medium. The various functions disclosed herein may be embodied in such program instructions, although some or all of the disclosed functions may alternatively be implemented in application-specific circuitry (e.g., ASICs or FPGAs) of the computer system. Where the computer system includes multiple computing devices, these devices may, but need not, be co-located. The results of the disclosed methods and tasks may be persistently stored by transforming physical storage devices, such as solid-state memory chips and/or magnetic disks, into a different state.

Although the subject matter contained herein has been described in detail for the purpose of illustration, it is to be understood that such detail is solely for that purpose and that the present disclosure is not limited to the disclosed embodiments, but, on the contrary, is intended to cover modifica-

62

tions and equivalent arrangements that are within the spirit and scope of the appended claims. For example, it is to be understood that the present disclosure contemplates that, to the extent possible, one or more features of any embodiment can be combined with one or more features of any other embodiment.

Other examples are within the scope and spirit of the description and claims. Additionally, certain functions described above can be implemented using software, hardware, firmware, hardwiring, or combinations of any of these. Features implementing functions can also be physically located at various positions, including being distributed such that portions of functions are implemented at different physical locations.

As used herein, a “neural network” refers to machine learning structures. Neural networks include one or more layers of “neurons” that each receive input information and produce an output as, for example, a weighted sum of the inputs with an optional internal bias value within the neuron, or some other predetermined function that produces an output numeric value based on a combination of the input values to the neuron. The weights that are assigned to different inputs in the structure of the neural network are produced during a training process for the neural network. A simple neural network includes an input layer of neurons connected to an output layer of neurons. The output layer of neurons is configured to produce outputs based on numeric functions applied to the inputs received at the output layer such as threshold functions with parameters that are produced during a training process. A neural network may include “deep” neural networks in which multiple layers of “hidden” neurons are arranged between the input layer and the output layer with varying structures for the hidden layers including fully connected layers where the output of a neuron in a first layer is connected to an input of each neuron in the next layer or partially connected layers where the outputs of neurons in a first layer are only connected to inputs of a portion of the neurons in the next layer.

A “pose” is the position and orientation of an object in a reference frame. In some embodiments, the pose is a position and orientation of a deformable laundry article. The pose can be specified by a position in two- (x,y) or three-dimensions (x,y,z) and a heading (θ). The pose can also be further specified by an orientation including a deformable shape or volume of the laundry article, which may take into account folds, creases, curves or other shapes and positions of the laundry article. The reference frame may be a global reference frame that is fixed to the environment or may be a relative reference frame that is in relationship to another object in the environment.

“Deformable” means that a shape of an article can be bent or folded. Deformable laundry articles are typically fabric clothing or washable household items as described herein. Deformable laundry articles do not typically hold a particular or stiff shape when lifted or manipulated.

“Intelligently sorted” refers to grouping or ordering articles, for example, by size, weight, shape, function, color, fabric type, washing and/or drying requirements or other characteristics.

What is claimed is:

1. A device for autonomously folding a deformable article, comprising:

a rotatable platform configured to receive the deformable article on a surface thereof;

at least one elongation in operable communication with at least one elongation drive, the at least one elongation configured to

63

raise and lower from the surface of the rotatable platform,
 move parallel to the surface, and
 fold the deformable article at one or more fold lines,
 a table drive configured to engage the rotatable platform 5
 and rotate the rotatable platform about a central axis
 such that the at least one elongation aligns with one fold
 line of the one or more fold lines for the deformable
 article;
 at least one sensor configured to detect a position and an 10
 orientation of the deformable article on the rotatable
 platform, the at least one sensor comprising one or
 more cameras calibrated at a fixed position and orientation
 relative to the platform; and
 at least one controller in operable communication with the 15
 at least one elongation drive, the table drive, and the at
 least one sensor.

2. The device of claim 1, wherein the at least one
 elongation comprises at least one clamp rod configured to 20
 raise and lower to clamp the at least one article against the
 platform at the fold line.

3. The device of claim 1, wherein the at least one
 elongation comprises at least one of a sweep rod and a planar
 blade.

4. The device of claim 1, wherein the at least one 25
 elongation comprises at least one of a circular, rectangular,
 square, diamond, triangular, oval, pentagonal, hexagonal,
 spline, and octagonal shaped cross section.

5. The device of claim 1, wherein the at least one 30
 elongation is configured to fold the deformable article by
 sliding under an edge of the deformable article parallel to
 the surface in a first direction toward one of the one or
 more fold lines,
 lifting a portion of the article off the surface,
 passing the lifted portion of the article over the fold line, 35
 and
 disposing the lifted portion atop another portion of the
 deformable article by slidably moving in the first
 direction at least until the article disengages from the at
 least one elongation. 40

6. The device of claim 5, wherein the at least one
 elongation is configured to engage a pair of driven carriers
 at opposite ends of the at least one elongation, the pair of
 driven carriers being slidably engaged with supports dis- 45
 posed on opposing sides of the rotatable platform, and
 wherein the pair of driven carriers comprise the at least one
 elongation drive configured to raise and lower the at least
 one elongation and to move the at least one elongation
 parallel to the surface.

7. The device of claim 1, wherein the table drive is 50
 configured to operate bi-directionally and wherein instruct-
 ing the table drive to rotate the platform comprises rotating
 the platform at least one of in a forward direction and in a
 reverse direction.

8. The device of claim 1, wherein the at least one sensor 55
 comprises at least one of a 3-D camera, an IR sensor, a 2-D
 camera, LIDAR, LADAR, a sonar proximity sensor, an
 ultrasonic ranging sensor, a radar sensor, and a pair of stereo
 depth cameras.

9. The device of claim 8, wherein the at least one 60
 controller is configured to receive an output signal compris-
 ing at least one of 2-D and 3-D image data of the deformable
 article.

10. The device of claim 9, wherein the output signal 65
 comprises presence value data indicative of a position of and
 orientation of the deformable article on the surface of the
 rotatable platform.

64

11. The device of claim 1, wherein the at least one
 controller is configured to, iteratively,
 receive one or more output signals from the at least one
 sensor,
 determine, based on the received one or more output
 signals, at least one of an article type, size, thickness,
 position, and orientation of the deformable article on
 the platform,
 determine based on the at least one of the determined
 article type, determined article size, determined article
 thickness, position, and orientation, one fold line of the
 one or more fold lines of the deformable article, and
 instruct the table drive to rotate the platform to align the
 determined one fold line of the deformable article with
 the at least one elongation suspended above the plat-
 form.

12. The device of claim 11, wherein the table drive is
 configured to rotate one or more times for alignment of the
 at least one elongation with two or more fold lines of the one
 or more fold lines.

13. The device of claim 12, wherein the at least one
 controller is configured to instruct the at least one elongation
 to fold the deformable article at the one or more fold lines
 to achieve a final folded state that is at or within a prede-
 termined footprint area.

14. The device of claim 1, wherein the one or more fold
 lines each comprise a line across at least a portion of the
 deformable article at which the at least one elongation is
 configured to fold the deformable article.

15. The device of claim 1, wherein the at least one
 controller is configured to dynamically determine a position
 and orientation of each of the one or more fold lines based
 on at least one of an accrued number of folds already
 executed and a determination of a difference in a maximum
 height and a minimum height of a top surface of the
 deformable article from the surface of the platform not being
 within or greater than a range between 1 to 3 inches.

16. The device of claim 1, wherein the deformable article
 is one of a plurality of deformable laundry articles compris- 40
 ing two or more article types of at least one of different sizes
 and different shapes, and wherein each of the two or more
 article types comprises a longest dimension of between
 about 4 cm to 500 cm.

17. The device of claim 16, wherein the platform is
 configured to sequentially receive a plurality of deformable
 articles thereon, the plurality of deformable articles com-
 prising alternating non-identical article types of the two or
 more article types.

18. A method of autonomously folding a deformable
 article, comprising:

iterating a folding sequence one or more times, the folding
 sequence comprising

receiving, at at least one controller, one or more output
 signals from one or more sensors in communication
 with the at least one controller, the one or more
 sensors being configured to at least one of detect one
 or more features and capture one or more images of
 a deformable article disposed on a platform,

determining, based on the at least one of the one or
 more features and one or more images, at least one
 of an article type, an article size, and an article
 thickness, wherein determining the article type com-
 prises processing the received output signal of the
 one or more sensors with a neural network classifier,
 determining, based on the determine at least one of the
 article type, article size, and article thickness, a fold
 line of the deformable article,

65

instructing a drive motor to rotate the platform to align the fold line with an elongated member suspended above and elongated parallel to a surface of the platform, and

instructing the elongated member to

slidably move in a first direction over the platform toward the fold line, the elongated member being disposed between the deformable article and the surface,

raise the deformable article up and over the fold line while moving in the first direction over the platform until the article disengages from the elongated member, and

determine whether the deformable article comprises at least one final fold dimension; and

stopping iterating the folding sequence upon determining the deformable article comprises the at least one final fold dimension.

19. The method of claim **18**, wherein determining the fold line comprises determining one or more fold lines for at least one of folding in protrusions of the deformable article to a central rectangle, folding the article to at or within a target rectangle size and location on the platform, and recursively folding the deformable article to at or within a target rectangle size.

20. The method of claim **18**, wherein determining the fold line comprises determining one or more fold lines for at least one of folding pants, folding an open front article, folding shirts, folding hooded sweatshirts, and folding in accordance with a customer request submitted via a computer terminal or an application operating on a handheld device in communication with the controller via a remote communication network.

21. The method of claim **18**, wherein determining the fold line comprises, based on the output signal of each of the one or more sensors, determining one or more natural fold lines of the deformable article, the one or more natural fold lines comprising at least one of a bisector of the deformable article and a seam of the deformable article.

22. The method of claim **18**, wherein the drive motor is configured to operate bi-directionally and wherein instructing the drive motor to rotate the platform comprises rotating the platform at least one of in a forward direction and in a reverse direction.

23. The method of claim **18**, wherein the elongated member comprises at least one of a rod and a planar blade configured to be suspended over the platform.

24. The method of claim **23**, wherein the one or more sensors comprises at least one of a 3-D camera, an IR sensor, a 2-D camera, LIDAR, LADAR, a sonar proximity sensor, an ultrasonic ranging sensor, a radar sensor, and a pair of stereo depth cameras.

25. The method of claim **24**, wherein the controller is configured to receive an output signal comprising at least one of 3-D image data of the deformable article and one or more 2-D images of the deformable article.

26. The method of claim **25**, wherein determining article type comprises performing a comparison to classified images stored in a memory in communication with the controller.

27. A device for autonomously folding a deformable article, comprising:

a rotatable platform configured to receive the deformable article on a surface thereof;

at least one elongation in operable communication with at least one elongation drive, the at least one elongation configured to

66

raise and lower from the surface of the rotatable platform,

move parallel to the surface, and

fold the deformable article at one or more fold lines,

a table drive configured to engage the rotatable platform and rotate the rotatable platform about a central axis such that the at least one elongation aligns with one fold line of the one or more fold lines for the deformable article;

at least one sensor configured to detect a position and an orientation of the deformable article on the rotatable platform; and

at least one controller in operable communication with the at least one elongation drive, the table drive, and the at least one sensor, the at least one sensor being configured to receive one or more folding instructions from a remote device in operable communication with the at least one controller via a wired or wireless network, wherein the one or more folding instructions comprise user inputs to at least one of a computer portal and smartphone application representative of one or more user inputs.

28. The device of claim **27**, wherein the one or more user inputs comprises at least one of a preferred at least one final dimension for the deformable article, a request for not folding the deformable article, a submission of an article type for the deformable article, one or more specified fold lines, and a preferred sequence for folding the deformable article at each of the one of the one or more specified fold lines.

29. A device for autonomously folding a deformable article, comprising:

a rotatable platform configured to receive the deformable article on a surface thereof;

at least one elongation in operable communication with at least one elongation drive, the at least one elongation configured to

raise and lower from the surface of the rotatable platform,

move parallel to the surface, and

fold the deformable article at one or more fold lines,

a table drive configured to engage the rotatable platform and rotate the rotatable platform about a central axis such that the at least one elongation aligns with one fold line of the one or more fold lines for the deformable article;

at least one sensor configured to detect a position and an orientation of the deformable article on the rotatable platform, wherein the at least one sensor comprises at least one of a 3-D camera, an IR sensor, a 2-D camera, LIDAR, LADAR, a sonar proximity sensor, an ultrasonic ranging sensor, a radar sensor, and a pair of stereo depth cameras; and

at least one controller in operable communication with the at least one elongation drive, the table drive, and the at least one sensor, the at least one controller being configured to receive an output signal comprising at least one of 2-D and 3-D image data of the deformable article, wherein the output signal comprises presence value data indicative of the position of and orientation of the deformable article on the surface of the rotatable platform.

30. A device for autonomously folding a deformable article, comprising:

a rotatable platform configured to receive the deformable article on a surface thereof;

67

at least one elongation in operable communication with at least one elongation drive, the at least one elongation configured to raise and lower from the surface of the rotatable platform, 5
 move parallel to the surface, and
 fold the deformable article at one or more fold lines, 5
 a table drive configured to engage the rotatable platform and rotate the rotatable platform about a central axis one or more times such that the at least one elongation aligns with two or more fold lines of the one or more fold lines; 10
 at least one sensor configured to detect a position and an orientation of the deformable article on the rotatable platform; and 15
 at least one controller in operable communication with the at least one elongation drive, the table drive, and the at least one sensor, the at least one controller being configured to achieve a final folded state that is at or within a predetermined footprint area by iteratively one 20
 or more times
 receiving one or more output signals from the at least one sensor,
 determining, based on the received one or more output signals, at least one of an article type, size, thickness, 25
 and position of the deformable article on the rotatable platform,
 determining based on the at least one of the determined article type, determined article size, determined article thickness, and the position, one fold line of 30
 the two or more fold lines of the deformable article,
 instructing the table drive to rotate the platform to align the determined one fold line of the deformable article with the at least one elongation suspended above the platform, and 35
 instructing the at least one elongation to fold the deformable article at the one fold line.

31. A device for autonomously folding a deformable article, comprising: 40
 a rotatable platform configured to receive the deformable article on a surface thereof;
 at least one elongation in operable communication with at least one elongation drive, the at least one elongation configured to raise and lower from the surface of the rotatable platform, 45
 form,
 move parallel to the surface, and
 fold the deformable article at one or more fold lines,
 a table drive configured to engage the rotatable platform and rotate the rotatable platform about a central axis 50
 such that the at least one elongation aligns with one fold line of the one or more fold lines for the deformable article;
 at least one sensor configured to detect a position and an orientation of the deformable article on the rotatable 55
 platform; and

68

at least one controller in operable communication with the at least one elongation drive, the table drive, and the at least one sensor, the at least one controller being configured to dynamically determine a position and orientation of each of the one or more fold lines based on at least one of an accrued number of folds already executed and a determination of a difference in a maximum height and a minimum height of a top surface of the deformable article from the surface of the platform not being within or greater than a range between 1 to 3 inches.

32. A method of autonomously folding a deformable article, comprising:
 iterating a folding sequence one or more times, the folding sequence comprising
 receiving, at at least one controller, one or more output signals from one or more sensors in communication with the at least one controller, the one or more sensors being configured to at least one of detect one or more features and capture one or more images of a deformable article disposed on a platform,
 determining, based on the at least one of the one or more features and one or more images, at least one of an article type, an article size, and an article thickness,
 determining, based on the determine at least one of the article type, article size, and article thickness, a fold line of the deformable article, wherein determining the fold line comprises, based on the output signal of each of the one or more sensors, determining one or more natural fold lines of the deformable article, the one or more natural fold lines comprising at least one of a bisector of the deformable article and a seam of the deformable article,
 instructing a drive motor to rotate the platform to align the fold line with an elongated member suspended above and elongated parallel to a surface of the platform, and
 instructing the elongated member to
 slidably move in a first direction over the platform toward the fold line, the elongated member being disposed between the deformable article and the surface,
 raise the deformable article up and over the fold line while moving in the first direction over the platform until the article disengages from the elongated member, and
 determine whether the deformable article comprises at least one final fold dimension; and
 stopping iterating the folding sequence upon determining the deformable article comprises the at least one final fold dimension.

* * * * *